

CA Nimsoft® Unified Dashboards

User Documentation



Document Revision History

Document Version	Date	Changes
1.0	March 30, 2012	New dashboards documented: <ul style="list-style-type: none">■ EMC Clariion■ EMC Celerra■ EMC VMAX■ IBM DS4K■ MS Exchange 2010■ MS SharePoint Server Updated documentation: <ul style="list-style-type: none">■ Amazon AWS■ MS Exchange 2007 First version of this document as separate from UMP help.
1.1	July 27, 2012	Added Troubleshooting section.
1.2	March 29, 2013	New dashboards documented: <ul style="list-style-type: none">■ Vcloud Updated dashboards documented: <ul style="list-style-type: none">■ VMware
1.3	June 28, 2013	New dashboards documented: <ul style="list-style-type: none">■ CloudStack

Legal Notices

Copyright © 2013, CA. All rights reserved.

Warranty

The material contained in this document is provided "as is," and is subject to being changed, without notice, in future editions. Further, to the maximum extent permitted by applicable law, Nimsoft LLC disclaims all warranties, either express or implied, with regard to this manual and any information contained herein, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. Nimsoft LLC shall not be liable for errors or for incidental or consequential damages in connection with the furnishing, use, or performance of this document or of any information contained herein. Should Nimsoft LLC and the user have a separate written agreement with warranty terms covering the material in this document that conflict with these terms, the warranty terms in the separate agreement shall control.

Technology Licenses

The hardware and/or software described in this document are furnished under a license and may be used or copied only in accordance with the terms of such license.

No part of this manual may be reproduced in any form or by any means (including electronic storage and retrieval or translation into a foreign language) without prior agreement and written consent from Nimsoft LLC as governed by United States and international copyright laws.

Restricted Rights Legend

If software is for use in the performance of a U.S. Government prime contract or subcontract, Software is delivered and licensed as "Commercial computer software" as defined in DFAR 252.227-7014 (June 1995), or as a "commercial item" as defined in FAR 2.101(a) or as "Restricted computer software" as defined in FAR 52.227-19 (June 1987) or any equivalent agency regulation or contract clause. Use, duplication or disclosure of Software is subject to Nimsoft LLC's standard commercial license terms, and non-DOD Departments and Agencies of the U.S. Government will receive no greater than Restricted Rights as defined in FAR 52.227-19(c)(1-2) (June 1987). U.S. Government users will receive no greater than Limited Rights as defined in FAR 52.227-14 (June 1987) or DFAR 252.227-7015 (b)(2) (November 1995), as applicable in any technical data.

Trademarks

Nimsoft is a trademark of CA.

Adobe®, Acrobat®, Acrobat Reader®, and Acrobat Exchange® are registered trademarks of Adobe Systems Incorporated.

Intel® and Pentium® are U.S. registered trademarks of Intel Corporation.

Java(TM) is a U.S. trademark of Sun Microsystems, Inc.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

Netscape(TM) is a U.S. trademark of Netscape Communications Corporation.

Oracle® is a U.S. registered trademark of Oracle Corporation, Redwood City, California.

UNIX® is a registered trademark of the Open Group.

ITIL® is a Registered Trade Mark of the Office of Government Commerce in the United Kingdom and other countries.

All other trademarks, trade names, service marks and logos referenced herein belong to their respective companies.

For information on licensed and public domain software, see the *Nimsoft Monitor Third-Party Licenses and Terms of Use* document at: http://docs.nimsoft.com/prodhelp/en_US/Library/index.htm?toc.htm?1981724.html.

Contact CA Nimsoft

Contact CA Support

For your convenience, CA Technologies provides one site where you can access the information that you need for your Home Office, Small Business, and Enterprise CA Technologies products. At <http://ca.com/support>, you can access the following resources:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- CA Support policies and guidelines
- Other helpful resources appropriate for your product

Providing Feedback About Product Documentation

Send comments or questions about CA Technologies Nimsoft product documentation to nimsoft.techpubs@ca.com.

To provide feedback about general CA Technologies product documentation, complete our short customer survey which is available on the CA Support website at <http://ca.com/docs>.

Contents

Chapter 1: Unified Dashboards Overview	11
Chapter 2: Update Dashboards	13
Chapter 3: Amazon AWS	15
AWS Required Data Sources	15
AWS Deployment Time	16
AWS Instance Overview	16
AWS Instance CPU Usage Summary	17
AWS File Read/Write Time	17
AWS Instance Disk Read/Write Bytes	18
AWS Instance Disk Read/Write Operations	18
Chapter 4: Cisco	19
Cisco Required Data Sources	19
Cisco Device CPU Performance	20
Cisco Device Memory Performance	20
Cisco Device Buffer Misses	21
Cisco Device Environment Status	22
Chapter 5: CloudStack	23
CloudStack Required Data Sources	23
Host Performance	24
Zone Performance	25
Pod Performance	26
Instance Performance	27
System Infrastructure Health	28
Chapter 6: Datacenter	29
Datacenter Required Data Sources	29
Current Server Performance	30
Server Disk Space Usage	30
Network Response Time	30
URL Response Time (List)	31

Chapter 7: EMC Celerra **33**

EMC Celerra Required Data Sources	33
Datamovers Capacity Usage	34
Storage Groups and Volumes	34
Memory and CPU Performance	35
Storage Summary	35

Chapter 8: EMC Clariion **37**

EMC Clariion Required Data Sources	37
Storage IO Performance	38
Storage Processors Performance	39
Storage System Health	39
Thin Pools Usage	40

Chapter 9: EMC VMAX **41**

EMC VMAX Required Data Sources	41
System IO Performance	42
System Health	43
System Data Throughput	43
Front-End Directors Status	44

Chapter 10: IBM DS4K **45**

IBM DS4K Required Data Sources	45
IBM DS4K Status Definitions	46
Storage Array Status	47
Disks Status	48
Storage Pool Status	48
Component Status	49
Controller Status	49
Port Status	50
LUN Status	50

Chapter 11: MS Exchange 2007 **53**

MS Exchange Required Data Sources	53
Memory Performance	55
Processor Utilization	56
Disk Performance	56
IS Queues Msg Opens/Sec	57
IS Send/Receive Queue Size	57

Exchange SMTP Queues	57
Exchange Transport Role Queues	58
Exchange MTA Queues.....	58
Exchange Server Load	58

Chapter 12: MS Exchange 2010 **59**

MS Exchange 2010 Required Data Sources.....	60
Processor Counters Exchange 2010	63
Memory Performance Exchange 2010.....	64
Transport Queues Exchange 2010	64
Exchange 2010 Domain Controllers Connectivity Counters.....	65
Network Counters Exchange 2010	66
Read Time Processes	66
Search Time Processes	67
.NET time in GC	67
.NET Exceptions Per Second	67
.NET Bytes in All Heaps.....	67

Chapter 13: MS Exchange 2013 **69**

MS Exchange 2013 Required Data Sources.....	70
LDAP	72
Memory Counters	72
Memory Private Bytes.....	72
Memory Virtual Bytes	73
Network Counters Exchange 2013	73
Processor Counters Exchange 2013	73
Search Time Processes	74
Read Time Processes	74
.NET Exceptions Thrown.....	75
.NET time in GC	75
.NET Bytes in All Heaps.....	75

Chapter 14: MS SharePoint Server **77**

SharePoint Required Data Sources	77
CPU Performance	80
Memory Usage and Performance	80
ASP.NET	81
Network Utilization	81
Disk Usage and Performance	82
SQL Server Statistics	82

W3WP Process	83
Web Front End Server	83

Chapter 15: MS SQL Server **85**

MS SQL Server Required Data Sources.....	85
Performance Reports Designer	86
Server Load.....	86
Locks.....	87
MS SQL Server Processes	87
Database Performance.....	87
User Statistics.....	88

Chapter 16: Network **89**

Network Required Data Sources	89
Web Site Response Time	90
Cisco Device Health	90
Ping Response Time	90
Interface Bandwidth.....	91

Chapter 17: Power **93**

Power Required Data Sources.....	93
UPS Battery Runtime Remaining.....	93
Data Center Power Effectiveness	94
Data Center Infrastructure Efficiency.....	94
UPS Input Line Voltage	94

Chapter 18: Server **95**

Server Required Data Sources.....	95
Current Server Performance	95
Server Load 1 hour average	96
Server Disk Space Usage.....	96

Chapter 19: Storage **97**

Storage Required Data Sources.....	98
Storage IOPS	100
Storage IO Data Rate	101
Storage Systems Status	101
Number of Storage Devices.....	101
Storage Systems Physical Disks	102

Chapter 20: Vblock	103
Vblock Required Data Sources	104
Vblock Storage Performance.....	110
Vblock UCS Performance.....	111
Vblock Nexus Switch Performance.....	111
Vblock Host Summary	111
Vblock Datastore Freespace.....	112
Vblock Guest Summary	112
Chapter 21: VCloud	115
VCloud Required Data Sources.....	115
VCloud Organization VDCs CPU Used Percent	116
VCloud Organization VDCs Memory Used Percent	116
VCloud Organization VDCs Storage Used Percent.....	117
VCloud Provider VDCs CPU Used Percent	118
VCloud Provider VDCs Memory Used Percent	118
VCloud Provider VDCs Storage Used Percent.....	119
Chapter 22: VMware	121
VMware Required Data Sources	121
VMware Host VM Count	123
VMware Guests	126
VMware Datastore Free Space.....	130
VMware Resource Pools	130
Chapter 23: Xenserver	133
Xenserver Required Data Sources	133
Xenserver CPU Metrics.....	134
Xenserver Network Metrics	134
Xenserver Memory Metrics VM	135
Xenserver Memory Metrics Host	135
Xenserver Disk Metrics.....	135
Xenserver Disk Usage Percentage	136

Chapter 1: Unified Dashboards Overview

The Unified Management Portal (UMP) comes with predefined views, called Unified Dashboards. To see a Unified Dashboard, click on the Unified Dashboards tab and select the dashboard you want to view.

In any of the dashboards, click a column header to sort by that column.

Chapter 2: Update Dashboards

New Unified Dashboards are released periodically, either as part of an UMP release or as a standalone package. These updated Unified Dashboards are *not* applied automatically in existing UMP implementations, even if you upgrade to a newer version of UMP that contains updated Unified Dashboards. To update Unified Dashboards with an existing UMP implementation, you must download the Unified Dashboard package from the Nimsoft support site, and then manually import the dashboards into UMP.

New installations of UMP automatically have the Unified Dashboards for that release.

Note: Upgrading to a newer version of UMP does *not* update Unified Dashboards in existing UMP implementations.

All users should check the Nimsoft support site periodically for updates and follow the procedure described here to update Unified Dashboards as appropriate.

Follow these steps:

1. Download the **unified_dashboards** probe package from the **Downloads** page at [Nimsoft support](#) to your local archive.
2. Drag the **unified_dashboards** package onto a robot where the wasp probe is running.

If the package icon turns red and you see a message stating **inst_execute failed error**, make sure wasp is running on the robot and then drag the package onto the robot again.
3. If you are running a version of UMP earlier than UMP 2.6.2, restart wasp.
Beginning with UMP 2.6.2, it is not necessary to restart wasp.
4. Point your browser to `http://<umpServer>[:port]/listdesigner/jsp/get_lar.jsp`.
5. Click on the names of the Unified Dashboards you want to update. Or, click on **UnifiedDashboards.lar** to get the latest version of all Unified Dashboards.

This prompts you to save the dashboard files to a folder on your client system.
6. Log into UMP.
7. Click **Manage, Control Panel** on the menu bar.
8. Click **My Pages**.
9. Click **Private Pages**.
10. Click **Export/Import**, then click **Import**.

11. Click **Browse** and choose a dashboard file.
Note: Importing a dashboard file overwrites your existing dashboard.
12. Leave the default options selected and click **Import**.
13. Repeat the above steps to import all the downloaded dashboard files you want to update.
14. Click the **Back to My Private Pages** link at the top of the page.

Chapter 3: Amazon AWS

The Amazon Web Services (AWS) Unified Dashboard provides predefined list views with key performance indicators for your AWS environment including individual instance performance, deployment time, file read times, and more.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[AWS Required Data Sources](#) (see page 15)

[AWS Deployment Time](#) (see page 16)

[AWS Instance Overview](#) (see page 16)

[AWS Instance CPU Usage Summary](#) (see page 17)

[AWS File Read/Write Time](#) (see page 17)

[AWS Instance Disk Read/Write Bytes](#) (see page 18)

[AWS Instance Disk Read/Write Operations](#) (see page 18)

AWS Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the AWS dashboard.

Probe	QoS Required	Subkey/Target
aws	QOS_MachineDeploymentTime	Deployment Time
	QOS_FileReadTime	File Transfer Time
	QOS_FileWriteTime	File Transfer Time
	QOS_CPUUtilization	Minimum Maximum Average
	QOS_DiskReadBytes	Average
	QOS_DiskWriteBytes	Average
	QOS_DiskReadOps	Average
	QOS_DiskWriteOps	Average

Probe	QoS Required	Subkey/Target
aws	QOS_MachineDeploymentTime	Deployment Time
	QOS_FileReadTime	File Transfer Time
	QOS_NetworkIn	Average
	QOS_NetworkOut	Average

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

AWS Deployment Time

Column	Description
AWS Instance ID	The AWS instance ID provided by Amazon. Click the name of an instance to view a Performance Report of deployment time data for that instance.
Last Deployment Time	Time, in seconds, it took to deploy a new Amazon instance.
Deployment Time	Mini-graph displaying the time, in seconds, it took to deploy a new Amazon instance.

AWS Instance Overview

Column	Description
Instance ID	The AWS instance ID provided by Amazon.
Alarm	Indicates an alarm associated with the instance.
CPU Usage	Gauge displaying the percentage of allocated EC2 compute units that are currently in use on the instance. This metric identifies the processing power required to run an application upon a selected instance. 0 to 49.99 = Green 50 to 79.99 = Orange 80 to 100 = Red
Network In	Mini-graph displaying the number of bytes received on all network interfaces by the instance. This metric identifies the volume of incoming network traffic to an application on a single instance.

Network Out	Mini-graph displaying the number of bytes sent out on all network interfaces by the instance. This metric identifies the volume of outgoing network traffic to an application on a single instance.
-------------	---

AWS Instance CPU Usage Summary

Column	Description
AWS Instance ID	The AWS instance ID provided by Amazon.
Min CPU	Minimum percentage of CPU in use.
Max CPU	Maximum percentage of CPU in use.
Avg CPU	Average percentage of CPU in use.
Avg CPU	Mini-graph displaying the average percentage of CPU in use for the previous hour.

AWS File Read/Write Time

Column	Description
AWS Instance ID	The AWS instance ID provided by Amazon. Click the name of an instance to view a Performance Report of file read/write time data for that instance.
Read	Number of seconds to read a file from the S3 storage service to the probe.
Read	Mini-graph displaying the number of seconds to read a file from the S3 storage service to the probe for the previous two hours.
Write	Number of seconds to write a file to the S3 storage service from the probe.
Write	Mini-graph displaying the number of seconds to write a file to the S3 storage service from the probe for the previous two hours.

AWS Instance Disk Read/Write Bytes

Column	Description
AWS Instance ID	The AWS instance ID provided by Amazon.
Read Bytes	Bytes read from all disks available to the instance. This metric is used to determine the volume of the data the application reads from the hard disk of the instance. This can be used to determine the speed of the application for the customer.
Avg Read Bytes	Mini-graph displaying the average Read Byte values for the previous two hours.
Write Bytes	Bytes written to all disks available to the instance. This metric is used to determine the volume of the data the application writes onto the hard disk of the instance. This can be used to determine the speed of the application for the customer.
Avg Write Bytes	Mini-graph displaying the average Write Byte values for the previous two hours.

AWS Instance Disk Read/Write Operations

Column	Description
AWS Instance ID	The AWS instance ID provided by Amazon.
Read Ops	Completed read operations from all disks available to the instances. This metric identifies the rate at which an application reads a disk. This can be used to determine the speed at which an application reads data from a hard disk.
Avg Read Ops	Mini-graph displaying the average Read Ops values for the previous hour.
Write Ops	Completed write operations to all hard disks available to the instance. This metric identifies the rate at which an application writes to a hard disk. This can be used to determine the speed at which an application saves data to a hard disk.
Avg Write	Mini-graph displaying the average Write Ops values for the previous hour.

Chapter 4: Cisco

The Cisco Unified Dashboard provides four predefined list views with performance and status information about Cisco devices in your environment.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [Cisco Required Data Sources](#) (see page 19)
- [Cisco Device CPU Performance](#) (see page 20)
- [Cisco Device Memory Performance](#) (see page 20)
- [Cisco Device Buffer Misses](#) (see page 21)
- [Cisco Device Environment Status](#) (see page 22)

Cisco Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the Cisco dashboard.

Probe	Qos Metric	SubKey/Target
cisco_monitor	QOS_CISCO_BUFFER_MISSES	Small Buffer Misses Medium Buffer Misses Big Buffer Misses Large Buffer Misses Very Large Buffer Misses Huge Buffer Misses
	QOS_CISCO_ENVIRONMENT	Fan State (0)
cdm	QOS_CPU_USAGE	CPU Last 5 sec CPU Last 1 min CPU Last 5 min

	QOS_MEMORY_USAGE	Memory Used Memory Free
	QOS_MEMORY_PERC_USAGE	Memory Percent Free

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Cisco Device CPU Performance

Column	Description
Host	IP address of the Cisco device.
Last 5 sec	Overall CPU busy percentage during the last 5-second period. 0 to 80 = Green 80 to 90 = Orange 90 to 100 = Red
Last 1 min	Overall CPU busy percentage during the last 1-minute period. 0 to 80 = Green 80 to 90 = Orange 90 to 100 = Red
Last 5 min	Overall CPU busy percentage during the last 5-minute period. 0 to 80 = Green 80 to 90 = Orange 90 to 100 = Red

Cisco Device Memory Performance

Column	Description
Host	IP address of the Cisco device.
Used	Number of megabytes of memory used during the last 5 minutes.
Free	Number of megabytes of memory available during the last 5 minutes.

Percent Free	Percent of memory available during the last 5 minutes. 20 to 100 = Green 10 to 20 = Orange 0 to 10 = Red
--------------	---

Cisco Device Buffer Misses

The processor memory of the Cisco device is divided into pools. Each pool contains a number of memory blocks of equal size. These memory blocks are called buffers.

There are six buffer pools:

- Small - 104-byte buffers
- Medium - 600-byte buffers
- Big - 1524-byte buffers
- Large - 4520-byte buffers
- Very Large - 5024-byte buffers
- Huge - 18024-byte buffers

Column	Description
Host	IP address of the Cisco device.
Small	Number of buffer misses for the small buffer pool during the last 5 minutes.
Medium	Number of buffer misses for the medium buffer pool during the last 5 minutes.
Big	Number of buffer misses for the big buffer pool during the last 5 minutes.
Large	Number of buffer misses for the large buffer pool during the last 5 minutes.
Very Large	Number of buffer misses for the very large buffer pool during the last 5 minutes.
Huge	Number of buffer misses for the huge buffer pool during the last 5 minutes.

Cisco Device Environment Status

Column	Description
Host	IP address of the Cisco device.
Fan State	Status of the device fan during the last 5 minutes. Status is reported as normal, warning, critical, shutdown, not present, or not functioning.

Chapter 5: CloudStack

The CloudStack Unified Dashboard provides predefined list views with information about the performance and health of the CloudStack environment. CloudStack refers to Apache CloudStack and Citrix CloudPlatform Powered by Apache CloudStack. The CloudStack Unified Dashboard provides information about performance of hosts, zones, pods, and VM instances, and about the health status of infrastructure components.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[CloudStack Required Data Sources](#) (see page 23)

[Host Performance](#) (see page 24)

[Zone Performance](#) (see page 25)

[Pod Performance](#) (see page 26)

[Instance Performance](#) (see page 27)

[System Infrastructure Health](#) (see page 28)

CloudStack Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated in order to populate data in the CloudStack dashboard.

Probe	QoS	Subkey/ Target
cloudstack	QOS_CLOUDSTACK_HOST_CPU_USED	Current CPU Used
	QOS_CLOUDSTACK_HOST_MEM_USED	Memory Used
	QOS_CLOUDSTACK_HOST_MEM_TOTAL	*
	QOS_CLOUDSTACK_ZONE_CPU_PCT_USED	*
	QOS_CLOUDSTACK_ZONE_MEMORY_PCT_USED	*
	QOS_CLOUDSTACK_ZONE_ALLOCATED_STORAGE_PCT_USED	*
	QOS_CLOUDSTACK_ZONE_DIRECT_IP_PCT_USED	*
	QOS_CLOUDSTACK_ZONE_PRIVATE_IP_PCT_USED	*

Probe	QoS	Subkey/ Target
	QOS_CLOUDSTACK_ZONE_PUBLIC_IP_PCT_USED	*
	QOS_CLOUDSTACK_POD_CPU_USAGE	*
	QOS_CLOUDSTACK_POD_MEMORY_PCT_USED	*
	QOS_CLOUDSTACK_POD_STORAGE_PCT_USED	*
	QOS_CLOUDSTACK_POD_PRIVATE_IP_PCT_USED	*
	QOS_CLOUDSTACK_VM_STATUS	VM Status
	QOS_CLOUDSTACK_VM_CPU_NUMBER	*
	QOS_CLOUDSTACK_VM_CPU_SPEED	*
	QOS_CLOUDSTACK_VM_CPU_USED	*
	QOS_CLOUDSTACK_VM_MEM_ALLOC	Memory
	QOS_CLOUDSTACK_VM_NET_READ	Network Kbs Read
	QOS_CLOUDSTACK_VM_NET_WRITE	Network Kbs Write
	QOS_CLOUDSTACK_SYS_VM_STATE	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Host Performance

This view displays information about the performance of CloudStack server hosts.

Column	Description
Host	<p>IP address or host name of system where the Citrix CloudStack server is running.</p> <p>Enter text in the filter field in the column header to see only hosts that contain that text. Click the arrow next to the filter field to toggle between descending and ascending sorting of the column values.</p>

Column	Description
CPU Usage	Percent of CPU used on the host in the last week. 0 to 70 = Green 71 to 80 = Yellow 81 to 90 = Orange 91 and above = Red
Memory Used in GB	Number of gigabytes of memory used on the host in the last week.
Total Memory	Number of megabytes of memory on the host in the last week.

Zone Performance

This view displays information about the performance of CloudStack zones.

Column	Description
Zones Performance	IP address or host name of the zone. Enter text in the filter field in the column header to see only zones that contain that text. Click the arrow next to the filter field to toggle between descending and ascending sorting of the column values.
CPU Used	Percent of allocated CPU in use in the last hour.
Memory Used	Percent of allocated memory in use in the last hour.
Allocated Storage Used	Percent of the storage allocated to the zone that is in use in the last hour.
Direct IP Used	Percent of direct IP addresses used by VM instances in the last hour.
Private IP Used	Percent of management IP addresses used by VM instances in the last hour.
Public IP Used	Percent of reserved system IP addresses, for this particular zone, used by VM instances in the last hour.

Pod Performance

This view displays information about the performance of CloudStack pods.

Column	Description
Host	IP address or host name of the system where the pod is running. Enter text in the filter field in the column header to see only pods that contain that text. Click the arrow next to the filter field to toggle between descending and ascending sorting of the column values.
Pod CPU Usage	Percent of host CPU in use by the pod in the last three weeks. 0 to 50 = Green 51 to 65 = Yellow 66 to 80 = Orange 81 and above = Red
Memory Usage	Percent of host memory in use by the pod in the last three weeks. 0 to 60 = Green 61 to 75 = Yellow 76 to 90 = Orange 91 and above = Red
Storage Usage	Percent of allocated storage in use by the pod in the last three weeks. 0 to 70 = Green 71 to 80 = Yellow 81 to 90 = Orange 91 and above = Red
Private IP Usage	Percent of management IP addresses used by pod in the last hour.

Instance Performance

This view displays information about the performance of virtual machine (VM) instances in the CloudStack environment.

Column	Description
VM Instances	IP address or host name of the system where the VM is running. Enter text in the filter field in the column header to see only VMs that contain that text.
Status	Status of the VM instance. Possible values are: <ul style="list-style-type: none"> ■ Running ■ Unknown ■ Starting ■ Migrating ■ Stopping ■ Stopped ■ Shut down ■ Destroyed ■ Expunging ■ Error
CPU Cores	Number of CPU cores allocated to the VM.
CPU Speed	Speed of the allocated CPU.
CPU Used in Mhz	Percent of allocated CPU capacity, in megahertz, in use in the last hour.
Memory Allocation	Amount of memory, in megabytes, allocated to the VM.
Network Reads	Number of kilobytes per second of data read from the network in the last hour.
Network Writes	Number of kilobytes per second of data written to the network in the last hour.

System Infrastructure Health

This view displays information about the health status of CloudStack infrastructure components.

Column	Description
CloudStack System	<p>IP address of the CloudStack system that runs the Admin REST API.</p> <p>Enter text in the filter field in the column header to see only CloudStack systems that contain that text. Click the arrow next to the filter field to toggle between descending and ascending sorting of the column values.</p>
System VM	<p>IP addresses of the system VMs that CloudStack manages to perform tasks in the cloud.</p> <p>Enter text in the filter field in the column header to see only system VMs that contain that text.</p>
State	<p>Status of the CloudStack system.</p> <p>Possible states are:</p> <ul style="list-style-type: none">■ Up■ Connecting■ Disconnected■ Creating■ Rebalancing■ Removed■ Down■ Alert■ Error

Chapter 6: Datacenter

The Datacenter Unified Dashboard provides predefined list views with key performance indicators for your data center infrastructure such as server health, disk space, network response, and web sites.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[Datacenter Required Data Sources](#) (see page 29)

[Current Server Performance](#) (see page 30)

[Server Disk Space Usage](#) (see page 30)

[Network Response Time](#) (see page 30)

[URL Response Time \(List\)](#) (see page 31)

Datacenter Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the Datacenter dashboard.

Probe	QoS	Subkey/Target
cdm	QOS_CPU_USAGE	\$HOST
	QOS_MEMORY_PERC_USAGE	\$HOST
net_connect	QOS_NET_CONNECT	*
url_response	QOS_URL_RESPONSE	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Current Server Performance

Column	Description
Host	Name of the host.
CPU Usage	Percent of CPU in use. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Memory Usage	Percent of memory in use. 0 to 69.99 = Green 70 to 89.99 = Orange 90 to 100 = Red
Alarm	Lists the alarms for the host.

Server Disk Space Usage

Column	Description
Host	Name of the host.
Disk	Name of the disk.
Percent Used	Highest percentage of disk space usage for hosts in the group for the last ten minutes.

Network Response Time

Column	Description
Monitored From	Name of host where Nimsoft Monitor is installed and monitoring response time.
Host:Port	Name and port type of the target host.
Resp Time	Time, in milliseconds, for a response to be received from the target host.
Resp Time	Gauge displaying the time, in milliseconds, for a response to be received from the target host.

URL Response Time (List)

Column	Description
Monitored From	Name of host where Nimsoft NM is installed and monitoring response time.
Monitored Site	The web site being monitored.
Resp Time	Time, in milliseconds, for a response to be received from the target URL.
Resp Time	Gauge displaying the time, in milliseconds, for a response to be received from the target URL.
Alarm	Indicates whether there is an alarm generated by the probe.

Chapter 7: EMC Celerra

The EMC Celerra Unified Dashboard provides predefined list views with information about the status and capacity of the EMC Celerra storage system.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [EMC Celerra Required Data Sources](#) (see page 33)
- [Datamovers Capacity Usage](#) (see page 34)
- [Storage Groups and Volumes](#) (see page 34)
- [Memory and CPU Performance](#) (see page 35)
- [Storage Summary](#) (see page 35)

EMC Celerra Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the EMC Celerra dashboard.

Probe	QoS	Subkey/ Target
celerra	QOS_STORAGE_RAW_TOTAL_CAPACITY	*
	QOS_STORAGE_RAW_FREE_CAPACITY_PERCENT	*
	QOS_STORAGE_NUM_OF_DISKS	*
	QOS_STORAGE_NUM_OF_DEVICES	*
	QOS_DMFS_TOTAL_CAPACITY	*
	QOS_DMFS_USED_CAPACITY	*
	QOS_DMFS_CAPACITY_FREE_PERCENT	*
	QOS_SVG_SIZE_TOTAL	*
	QOS_SVM_SIZE_TOTAL	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Datamovers Capacity Usage

Column	Description
Data Movers File Systems	Name of the data mover. Enter text in the filter field in the column header to see only data mover names that contain that text.
Total Capacity in KBytes	Number of kilobytes in the data mover.
Used Capacity in KBytes	Number of kilobytes used.
Capacity Free in percent	Percent of capacity not used. 75 to 100 = Green 50 to 76 = Yellow 11 to 49 = Orange 1 to 10 = Red

Storage Groups and Volumes

Column	Description
Celerra Systems	Name of the system that hosts the Celerra server. Enter text in the filter field in the column header to see only Celerra system names that contain that text.
Celerra System Details	Name of the storage volume. Enter text in the filter field in the column header to see only storage volumes that contain that text.
Storage Group Size	Size of the storage group.
Meta Volume Size	Size of the meta volume.

Memory and CPU Performance

Column	Description
Celerra Systems	Name of the system that hosts the Celerra server. Click the name of a host to view a Performance Report with memory and CPU data for that host. Enter text in the filter field in the column header to see only host names that contain that text.
Memory Free in KBytes	Number of kilobytes free on the host system.
CPU Free in percent	Percent of CPU not used. 50 to 100 = Green 25 to 50 = Yellow 10 to 25 = Orange 1 to 10 = Red

Storage Summary

Column	Description
Celerra Systems	Name of the system that hosts the Celerra server. Click the name of a host to view a Performance Report with performance data for that host. Enter text in the filter field in the column header to see only Celerra system names that contain that text.
Total Capacity	Number of gigabytes in the Celerra system.
Free Capacity	Percent of capacity not used. 50 to 100 = Green 25 to 50 = Yellow 10 to 25 = Orange 0 to 10 = Red
Total Disks	Number of disks.
Total Devices	Number of LUNs.

Chapter 8: EMC Clariion

The EMC Clariion Unified Dashboard provides predefined list views with information about the status and capacity of the EMC Clariion storage system.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[EMC Clariion Required Data Sources](#) (see page 37)

[Storage IO Performance](#) (see page 38)

[Storage Processors Performance](#) (see page 39)

[Storage System Health](#) (see page 39)

[Thin Pools Usage](#) (see page 40)

EMC Clariion Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the EMC Clariion dashboard.

Probe	QoS	Subkey/ Target
clariion	QOS_STORAGE_RAW_TOTAL_CAPACITY	*
	QOS_STORAGE_SYS_FAULTS	*
	QOS_STORAGE_TP_AVAILABLE_CAPACITY	*
	QOS_STORAGE_TP_CONSUMED_CAPACITY	*
	QOS_STORAGE_TP_PERCENT_FULL	*
	QOS_STORAGE_TP_PERCENT_SUBSCRIBED	*
	QOS_STORAGE_SP_BLOCKS_READ_PER_SECOND	SP A SP B
	QOS_STORAGE_SP_BLOCKS_WRITTEN_PER_SECOND	SP A SP B
	QOS_STORAGE_SP_READ_IOPS	SP A SP B

Probe	QoS	Subkey/ Target
	QOS_STORAGE_SP_WRITE_IOPS	SP A SP B
	QOS_STORAGE_SP_PCT_BUSY	*
	QOS_STORAGE_SP_PCT_DIRTY	SP A SP B
	QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPA	Fast Cache
	QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPB	Fast Cache

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Storage IO Performance

Column	Description
Clariion Systems	Name of the system that hosts the Clariion server. Click the name of a Clariion System to view a Performance Report with storage IO data for that system. Enter text in the filter field in the column header to see only Clariion System names that contain that text.
SP A - Blocks Read/Sec	Number of blocks per second read by storage processor A.
SP B - Blocks Read/Sec	Number of blocks per second read by storage processor B.
SP A - Blocks Written/Sec	Number of blocks per second written by storage processor A.
SP B - Blocks Written/Sec	Number of blocks per second written by storage processor B.
SP A - Read IOPS	Number of read operations per second by storage processor A.
SP B - Read IOPS	Number of read operations per second by storage processor B.
SP A - Write IOPS	Number of write operations per second by storage processor A.
SP B - Write IOPS	Number of write operations per second by storage processor B.

Storage Processors Performance

Column	Description
Clariion Systems	Name of the system that hosts the Clariion server. Click the name of a Clariion System to view a Performance Report with storage IO data for that system. Enter text in the filter field in the column header to see only Clariion System names that contain that text.
SP A - Pct Busy	Percent of time storage processor A is busy.
SP B - Pct Busy	Percent of time storage processor B is busy.
SP A - Pct Dirty	For storage processor A, percent of data that is in DRAM cache and has not been written to disk.
SP B - Pct Dirty	For storage processor B, percent of data that is in DRAM cache and has not been written to disk.
SP A - Fast Cache Pct Dirty	For storage processor A, percent of data that is in FLASH cache and has not been written to disk.
SP B - Fast Cache Pct Dirty	For storage processor B, percent of data that is in FLASH cache and has not been written to disk.

Storage System Health

Column	Description
Clariion Systems	Name of the system that hosts the Clariion server. Click the name of a Clariion System to view a Performance Report with storage IO data for that system. Enter text in the filter field in the column header to see only Clariion System names that contain that text.
Total Capacity	Number of gigabytes in the Clariion storage system.
System Health	Number of faults for the storage system. 0 = OK (Green) 1 or more = Failed (Red)

Thin Pools Usage

Column	Description
Storage Thin Pools	Name of the thin pool. Enter text in the filter field in the column header to see only thin pool names that contain that text.
Total Capacity	Number of gigabytes available in the thin pool.
Consumed Capacity	Number of gigabytes of the thin pool used.
Percent Full	Percent of thin pool capacity consumed. 0 to 75 = Green 75 to 85 = Yellow 85 to 95 = Orange 95 to 100 = Red
Percent Subscribed	Percent of thin pool capacity subscribed. 0 to 90 = Green 90 to 120 = Yellow 121 to 200 = Orange Greater than 200 = Red

Chapter 9: EMC VMAX

The EMC VMAX Unified Dashboard provides predefined list views with information about the status and capacity of the EMC VMAX storage system.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[EMC VMAX Required Data Sources](#) (see page 41)

[System IO Performance](#) (see page 42)

[System Health](#) (see page 43)

[System Data Throughput](#) (see page 43)

[Front-End Directors Status](#) (see page 44)

EMC VMAX Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the EMC VMAX dashboard.

Probe	QoS	Subkey/ Target
vmax	QOS_STORAGE_SYMM_WRITE_PER_SEC	*
	QOS_STORAGE_SYMM_READ_PER_SEC	*
	QOS_STORAGE_SYMM_DIR_I_O_PER_SEC	*
	QOS_STORAGE_SYMM_WRITE_HIT_RATIO	*
	QOS_STORAGE_SYMM_READ_HIT_RATIO	*
	QOS_STORAGE_SYMM_DISK_KB_READ_PER_SEC	*
	QOS_STORAGE_SYMM_DISK_KB_WRITE_PER_SEC	*
	QOS_STORAGE_SYMM_KB_READ_PER_SEC	*
	QOS_STORAGE_SYMM_KB_WRITE_PER_SEC	*
	QOS_STORAGE_SYMM_CACHE	*
	QOS_STORAGE_SYMM_DIR_READ_WRITE_CACHE_HIT_RATIO	*

Probe	QoS	Subkey/ Target
	QOS_STORAGE_RAW_FREE_CAPACITY_PERCENT	*
	QOS_STORAGE_SYMM_PERCENT_SUBSCRIBED	*
	QOS_STORAGE_DIR_OP_STATUS	*
	QOS_STORAGE_DIR_READ_PER_SEC	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

System IO Performance

Column	Description
Host	Name of the system that hosts the VMAX server. Click the name of a host to view a Performance Report with IO performance data for that host. Enter text in the filter field in the column header to see only host names that contain that text.
Write/Sec	Number of write requests per second for the array.
Read/Sec	Number of read requests per second for the array.
Dir I/O per Sec	Number of IO requests per second for all directors.
Write Hit ratio	Aggregated ratio of write requests for the array found in cache, as opposed to disk. The higher this number, the better the performance.
Read Hit Ratio	Aggregated ratio of read requests for the array found in cache, as opposed to disk. The higher this number, the better the performance.

System Health

Column	Description
Host	Name of the system that hosts the VMAX server. Click the name of a host to view a Performance Report with data for that host. Enter text in the filter field in the column header to see only host names that contain that text.
Cache Size	Total cache size.
Cache Hit Ratio	Aggregated ratio of read and write requests for the array found in cache, as opposed to disk. The higher this number, the better the performance. 70 to 100 = Green 20 to 70 = Yellow 10 to 20 = Orange 0 to 10 = Red
Raw Disk Free Capacity	Total capacity of all disks. 50 to 100 = Green 30 to 50 = Yellow 5 to 30 = Orange 0 to 5 = Red
Device Pool Subscribed	Percent of total disk capacity that is subscribed. 0 to 50 = Green 50.01 to 75 = Yellow 75.01 to 90 = Orange Greater than 90 = Red

System Data Throughput

Column	Description
Host	Name of the system that hosts the VMAX server. Click the name of a host to view a Performance Report with throughput data for that host. Enter text in the filter field in the column header to see only host names that contain that text.
Disk KB Read/Sec	Read rate for all disks in kilobytes per second.
Disk KB Write/Sec	Write rate for all disks in kilobytes per second.

Column	Description
Device KB Read/Sec	Read rate for all logical devices in kilobytes per second.
Device KB Write/Sec	Write rate for all logical devices in kilobytes per second.

Front-End Directors Status

Column	Description
Front-End Directors	Name of the director.
Op Status	Status of the director. Online = Green Other = Red
Read IO per sec	Read rate per second for the director.

Chapter 10: IBM DS4K

The IBM DS4K Unified Dashboard provides predefined list views with information about the status and performance of the IBM DS4K disk storage system.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[IBM DS4K Required Data Sources](#) (see page 45)

[IBM DS4K Status Definitions](#) (see page 46)

[Storage Array Status](#) (see page 47)

[Disks Status](#) (see page 48)

[Storage Pool Status](#) (see page 48)

[Component Status](#) (see page 49)

[Controller Status](#) (see page 49)

[Port Status](#) (see page 50)

[LUN Status](#) (see page 50)

IBM DS4K Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the IBM DS4K dashboard.

Probe	QoS	Subkey/ Target
ibm ds4k	QOS_STORAGE_COMPONENT_OPERATIONAL_STATUS	*
	QOS_STORAGE_SP_OPERATIONAL_STATUS	*
	QOS_STORAGE_ARRAY_TOTAL_MANAGED_SPACE	\$HOST *
	QOS_STORAGE_DISK_OPERATIONAL_STATUS	*
	QOS_STORAGE_DISK_KBYTES_READ_RATE	*
	QOS_STORAGE_DISK_KBYTES_WRITTEN_RATE	*
	QOS_STORAGE_VOL_OPERATIONAL_STATUS	*
	QOS_STORAGE_PORT_OPERATIONAL_STATUS	*

Probe	QoS	Subkey/ Target
	QOS_STORAGE_ARRAY_OPERATIONAL_STATUS	\$HOST
	QOS_STORAGE_ARRAY_REMAINING_MANAGED_SPACE	\$HOST
	QOS_STORAGE_POOL_CAPACITY_USED_PERCENT	\$HOST *
	QOS_STORAGE_ARRAY_READ_HIT_RATIO	\$HOST
	QOS_STORAGE_ARRAY_WRITE_HIT_RATIO	\$HOST
	QOS_STORAGE_POOL_OPERATIONAL_STATUS	*
	QOS_STORAGE_POOL_TOTAL_MANAGED_SPACE	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

IBM DS4K Status Definitions

The IBM DS4K Unified Dashboard displays the status of various components of the disk storage system. This table describes the possible statuses.

Color	Status	Description
Cyan	Unknown	Device status could not be determined.
Cyan	Other	Device status could not be determined.
Green	OK	Device is functioning properly.
Yellow	Degraded	Device is degraded or disabled. This usually means that device performance is not as expected.
Orange	Stressed	Device is experiencing a heavy load.
Red	Predictive failure	Device is in a failure mode that can be predicted by its parent.
Red	Error	Device is in an error state that can be identified by the device or its parent.
Red	Non-recoverable error	Device or its parent has detected an error that requires replacing the device.

Blue	Starting	Device is starting operation.
Blue	Stopping	Device is shutting down.
Blue	Stopped	Device has shut down.
Green	In service	Device is in operation.
Cyan	No contact	Client or parent device cannot contact the device.
Cyan	Lost communication	Client or parent device has lost communication with the device.
Yellow	Aborted	Device has aborted its normal operation.
Cyan	Dormant	Device is in sleep mode.
Red	Supporting entity in error	Child elements are in an error state.
Green	Completed	Device has completed operation.

Storage Array Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text. Click the name of an array to view a Performance Report with performance data for that storage array.
Status	Status of the storage array.
Total Capacity	Total capacity of all disks in the array.
Free Capacity	Number of gigabytes of total capacity not used.
Free Capacity	Gauge displaying the percentage of total capacity not used. 5 to 100 = Green 2 to 4.99 = Orange 0 to 1.99 = Red
Read Hit Ratio	Aggregated ratio of read requests for the array found in cache, as opposed to disk. The higher this number, the better the performance. 90 to 100 = Green 50 to 89.99 = Orange 0 to 49.99 = Red

Write Hit Ratio	Aggregated ratio of write requests for the array found in cache, as opposed to disk. The higher this number, the better the performance. 90 to 100 = Green 50 to 89.99 = Orange 0 to 49.99 = Red
-----------------	---

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Disks Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.
Disk	Name of the disk. Enter text in the filter field in the column header to see only disk names that contain that text.
Status	Status of the disk.
Read Rate	Rate, in kilobytes per second, at which data is read from disk.
Write Rate	Rate, in kilobytes per second, at which data is written to disk.

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Storage Pool Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.

Storage Pool	Name of storage pool. Enter text in the filter field in the column header to see only storage pool names that contain that text.
Status	Status of the storage pool.
Total Capacity	Number of gigabytes in the storage pool.
Used Capacity	Percent of total capacity of the storage pool used: 0 to 94.99 = Green 95 to 97.99 = Orange 98 to 100 = Red

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Component Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.
Component	Name of the component. Enter text in the filter field in the column header to see only component names that contain that text.
Status	Status of the component.

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Controller Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.

Controller	Name of the controller. Enter text in the filter field in the column header to see only controller names that contain that text.
Status	Status of the controller.

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Port Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.
Port	Port number in the controller. Enter a number in the filter field in the column header to see only ports that contain that number.
Status	Status of the port.

More information:

[IBM DS4K Status Definitions](#) (see page 46)

LUN Status

Column	Description
Storage Array	Name of the storage array. Enter text in the filter field in the column header to see only storage array names that contain that text.
LUN	The logical unit number (LUN) identifies a logical disk created on a SAN. Enter text in the filter field in the column header to see only LUNs that contain that text.
Status	Status of the LUN.

More information:

[IBM DS4K Status Definitions](#) (see page 46)

Chapter 11: MS Exchange 2007

The MS Exchange 2007 Server Unified Dashboard provides pre-defined list views with information about your Microsoft Exchange 2003 server and Microsoft Exchange 2007 server, such as load, processor time, queues, and disk performance.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[MS Exchange Required Data Sources](#) (see page 53)

[Memory Performance](#) (see page 55)

[Processor Utilization](#) (see page 56)

[Disk Performance](#) (see page 56)

[IS Queues Msg Opens/Sec](#) (see page 57)

[IS Send/Receive Queue Size](#) (see page 57)

[Exchange SMTP Queues](#) (see page 57)

[Exchange Transport Role Queues](#) (see page 58)

[Exchange MTA Queues](#) (see page 58)

[Exchange Server Load](#) (see page 58)

MS Exchange Required Data Sources

The MS Exchange 2007 Unified Dashboard requires these probes:

- exchange_monitor
- exchange_monitor_backend
- perfmon
- processes
- ntevl

This table lists the QoS metrics and subkeys or targets that must be activated on the probes to populate data in the MS Exchange 2007 dashboard.

QoS Required	Subkey/Target
QOS_MEMORY_PHYSICAL	*
QOS_MEMORY_PHYSICAL_PERC	*

QoS Required	Subkey/Target
QOS_EXCHANGE_MEMORY_AVAILABLE_MEGABYTES	*
QOS_EXCHANGE_MEMORY_PAGES_PER_SECOND	*
QOS_EXCHANGE_MEMORY_PAGING_FILE_USAGE	*
QOS_%_PROCESSOR_TIME	*
QOS_%_USER_TIME	*
QOS_EXCHANGE_IS_SEND_QUEUE_SIZE_-_PUBLIC_FOLDERSQOS_%_PRIVILEGED_TIME	*
QOS_EXCHANGE_DISK_AVERAGE_DISK_QUEUE_LENGTH	*
QOS_EXCHANGE_DISK_AVERAGE_DISK_BYTES_PER_TRANSFER	*
QOS_EXCHANGE_DISK_AVERAGE_DISK_SECONDS_PER_READ	*
QOS_EXCHANGE_DISK_AVERAGE_DISK_SECONDS_PER_WRITE	*
QOS_EXCHANGE_IS_MESSAGE_OPENS_PER_SECOND_-_MAILBOXES	*
QOS_EXCHANGE_IS_MESSAGE_OPENS_PER_SECOND_-_PUBLIC_FOLDERS	*
QOS_EXCHANGE_IS_RECEIVE_QUEUE_SIZE_-_MAILBOXES	*
QOS_EXCHANGE_IS_SEND_QUEUE_SIZE_-_MAILBOXES	*
QOS_EXCHANGE_IS_RECEIVE_QUEUE_SIZE_-_PUBLIC_FOLDERS	*
QOS_EXCHANGE_IS_SEND_QUEUE_SIZE_-_PUBLIC_FOLDERS	*
QOS_EXCHANGE_SMTP_LOCAL_QUEUE_LENGTH	Local Queue Length
QOS_EXCHANGE_SMTP_REMOTE_QUEUE_LENGTH	Remote Queue Length
QOS_EXCHANGE_TRANS_ROLE_AGGREGATE_DELIVERY_QUEUE_LENGTH_(ALL_QUEUES)	Aggregate Delivery Queue Length (All Queues)
QOS_EXCHANGE_TRANS_ROLE_POISON_QUEUE_LENGTH	Poison Queue Length
QOS_EXCHANGE_TRANS_ROLE_RETRY_MAILBOX_DELIVERY_QUEUE_LENGTH	Retry Mailbox Delivery Queue Length
QOS_EXCHANGE_TRANS_ROLE_UNREACHABLE_QUEUE_LENGTH	Unreachable Queue Length

QoS Required	Subkey/Target
QOS_EXCHANGE_MTA_CONNECTION_QUEUE_LENGTH	Connection Queue Length (PendingRerouteQ)
QOS_EXCHANGE_MTA_WORK_QUEUE_LENGTH	Work Queue Length
QOS_CPU_USAGE	

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Memory Performance

Column	Description
Host	Name of the host where the Exchange server is installed.
Physical Memory	Total amount of physical memory available to Windows.
Percent Physical Memory	Percentage of total amount of physical memory available to Windows. 0 to 50.99 = Green 51 to 75.99 = Yellow 76 to 89.99 = Orange 90 to 100 = Red
Available MB	The amount of physical memory immediately available for allocation to a process or for system use.
Pages/Sec	The rate at which pages are read from or written to disk to resolve hard page faults. This counter is a primary indicator of the kinds of faults that cause system-wide delays.

Paging File Usage	The percentage of a Page File instance in use. 0 to 50.99 = Green 51 to 59.99 = Yellow 60 to 74.99 = Orange 75 to 100 = Red
-------------------	---

Processor Utilization

Column	Description
Host	Name of the host where the Exchange server is installed.
Perc Processor Time	The percentage of elapsed time that the processor spends to execute a non-idle thread of the process. 0 to 74.99 = Green 75 to 100 = Red
Perc User Time	The percentage of processor time spent in user mode. 0 to 74.99 = Green 75 to 100 = Red
Perc Privileged Time	The percentage of processor time spent in privileged mode. 0 to 74.99 = Green 75 to 100 = Red

Disk Performance

Column	Description
Host	Name of the host where the Exchange server is installed.
Average Disk Queue Length	The average number of both read and write requests that were queued for the selected disk during the sample interval.
Average Disk Bytes/Transfer	The average number of bytes transferred to or from the disk during write or read operations.
Average Disk Seconds/Read	The average time to read data from the disk.
Average Disk Seconds/Write	The average time to write data to the disk.

IS Queues Msg Opens/Sec

Column	Description
Host	Name of the host where the Exchange server is installed.
Mailboxes 1 hr avg	This will show how often your users are opening messages within mailboxes. Peak load may show this coinciding with other system behavior.
Public Folders 1 hr avg	This will show how often your users are opening messages within public folders. Peak load may show this coinciding with other system behavior.

IS Send/Receive Queue Size

Column	Description
Host	Name of the host where the Exchange server is installed.
Mailbox Receive Queue Size	Number of messages received in mail boxes.
Mailbox Send Queue Size	Number of messages sent from mail boxes.
Public Folders Receive Queue Size	Number of messages received in public folders.
Public Folders Send Queue Size	Number of messages sent from public folders.

Exchange SMTP Queues

Column	Description
Host	Name of the host where the Exchange server is installed.
Local	Number of messages in the local SMTP queue.
Remote	Number of messages in remote SMTP queue.

Note: Data in this portlet will show up only for Exchange 2003 server setup.

Exchange Transport Role Queues

Column	Description
Host	Name of the host where the Exchange server is installed.
Messages	Aggregate Delivery Queue Length (All Queues) is the number of items queued for delivery in all queues.
Poison	The number of items in the poison queue.
Retry Mailbox Delivery	The number of items in the retry mailbox queues.
Unreachable	The number of items in the unreachable queues.

Exchange MTA Queues

Column	Description
Host	Name of the host where the Exchange server is installed.
Connection 1hr avg	Average MTA connection queue length during the last hour.
Work 1hr avg	Average MTA work queue length during the last hour.

Note: Data in this portlet will show up only for Exchange 2003 server setup.

Exchange Server Load

Column	Description
Host	Name of the host where the Exchange server is installed.
Processor Queue Length 1 hr	Number of processes queued for the Exchange server in the past hour.
Current CPU Usage	Percent of CPU consumed by the Exchange server. 0 to 80 = Green 80 to 90 = Orange 90 to 100 = Red

Chapter 12: MS Exchange 2010

The MS Exchange Server 2010 Unified Dashboard provides pre-defined list views with information about your Microsoft Exchange server 2010, such as processor, memory performance, transport queues, domain controllers, .Net framework, and network counters.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[MS Exchange 2010 Required Data Sources](#) (see page 60)

[Processor Counters Exchange 2010](#) (see page 63)

[Memory Performance Exchange 2010](#) (see page 64)

[Transport Queues Exchange 2010](#) (see page 64)

[Exchange 2010 Domain Controllers Connectivity Counters](#) (see page 65)

[Network Counters Exchange 2010](#) (see page 66)

[Read Time Processes](#) (see page 66)

[Search Time Processes](#) (see page 67)

[.NET time in GC](#) (see page 67)

[.NET Exceptions Per Second](#) (see page 67)

[.NET Bytes in All Heaps](#) (see page 67)

MS Exchange 2010 Required Data Sources

The MS Exchange 2007 Unified Dashboard requires these probes:

- exchange_monitor
- exchange_monitor_backend
- perfmon
- processes
- ntevl

This table lists the QoS metrics and subkeys or targets that must be activated to populate data in the MS Exchange 2010 dashboard.

QoS Required	Subkey/ Target
QOS_EXCHANGE_PROCESSOR_USER_TIME	User Time
QOS_EXCHANGE_PROCESSOR_PRIVILEGED_TIME	Privileged Time
QOS_EXCHANGE_PROCESSOR_PROCESSOR_QUEUE_LENGTH	
QOS_EXCHANGE_PROCESSOR_PROCESSOR_TIME	Processor Time
QOS_EXCHANGE_PROCESSOR_PROCESSOR_TIME_INSTANCE	Processor Time Instance (processes)

QoS Required	Subkey/ Target
QOS_EXCHANGE_PROCESSOR_USER_TIME	User Time
QOS_EXCHANGE_PROCESSOR_PRIVILEGED_TIME	Privileged Time
QOS_EXCHANGE_MEMORY_AVAILABLE_MBYTES	
QOS_EXCHANGE_MEMORY_POOL_PAGED_BYTES	Pool Paged Bytes
QOS_EXCHANGE_MEMORY_POOL_NONPAGED_MEGABYTES	Pool Nonpaged Megabytes
QOS_EXCHANGE_MEMORY_CACHE_BYTES	Cache Bytes
QOS_EXCHANGE_MEMORY_PRIVATE_BYTES	Private Bytes
QOS_EXCHANGE_MEMORY_VIRTUAL_BYTES	Virtual Bytes
QOS_EXCHANGE_TRANS_ROLE_AGGREGATE_DELIVERY_QUEUE_LENGTH_(ALL_QUEUES)-TRANSPORT	Aggregate Delivery Queue Length (All Queues) - Transport
QOS_EXCHANGE_TRANS_ROLE_ACTIVE_MAILBOX_DELIVERY_QUEUE_LENGTH-TRANSPORT	Active Mailbox Delivery Queue Length - Transport
QOS_EXCHANGE_TRANS_ROLE_RETRY_MAILBOX_DELIVERY_QUEUE_LENGTH-TRANSPORT	Retry Mailbox Delivery Queue Length - Transport
QOS_EXCHANGE_TRANS_ROLE_UNREACHABLE_QUEUE_LENGTH-TRANSPORT	Unreachable Queue Length - Transport
QOS_EXCHANGE_TRANS_ROLE_POISON_QUEUE_LENGTH-TRANSPORT	Poison Queue Length - Transport

QoS Required	Subkey/ Target
QOS_EXCHANGE_PROCESSOR_USER_TIME	User Time
QOS_EXCHANGE_PROCESSOR_PRIVILEGED_TIME	Privileged Time
QOS_EXCHANGE_TRANS_ROLE_MESSAGES_SUBMITTED_PER_SECOND	Messages Submitted Per Second
QOS_EXCHANGE_TRANS_ROLE_MESSAGES_COMPLETED_DELIVERY_PER_SECOND	Messages Completed Delivery Per Second
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCHES_PER_SECOND	LDAP Searches Per Second(0)
QOS_EXCHANGE_MSEXCHANGE_LDAP_READ_TIME_PROCESSES	LDAP Read Time Processes
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCH_TIME_PROCESSES	LDAP Search Time Processes
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCHES_TIMED_OUT_PER_MINUTE	LDAP Searches Timed Out Per Minute
QOS_EXCHANGE_MSEXCHANGE_LONG_RUNNING_LDAP_OPERATIONS_PER_MINUTE	Long Running LDAP Operations Per Minute
QOS_EXCHANGE_MEMORY_DOTNET - TIME_IN_GC	DOTNET Time in GC
QOS_EXCHANGE_MEMORY_DOTNET - EXCEPTION_THROWN_PER_SEC	Dotnet - Exception Thrown Per Sec
QOS_EXCHANGE_MEMORY_DOTNET - BYTES_IN_ALL_HEAPS	DOTNET - Bytes In All Heaps
QOS_EXCHANGE_NETWORK_KILO_BYTES_TOTAL_PER_SECOND	\$HOST
QOS_EXCHANGE_NETWORK_PACKETS_OUTBOUND_ERRORS	Packet Outbound Errors
QOS_EXCHANGE_NETWORK_TCPV4_CONNECTIONS_ESTABLISHED	TCPv4 Connections Established
QOS_EXCHANGE_NETWORK_TCPV6_CONNECTION_FAILURES	TCPv6 Connection Failures

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Processor Counters Exchange 2010

Column	Description
Host	Name of the host where the Exchange server is installed.
Processor User Time	Percentage of processor time spent in user mode. User mode is a restricted processing mode designed for applications, environment subsystems, and integral subsystems. 0 to 74.99 = Green 75 = Red
Processor Privileged Time	Percentage of processor time spent in privileged mode. Privileged mode is a processing mode designed for operating system components and hardware-manipulating drivers. It allows direct access to hardware and all memory. 0 to 74.99 = Green 75 = Red
Processor Queue Length	Number of threads each processor is servicing. Processor queue length can be used to identify whether processor contention or high CPU utilization is caused by the processor capacity being insufficient to handle the workload assigned to it. Processor Queue Length shows the number of threads that are delayed in the Processor Ready Queue and are waiting to be scheduled for execution. The listed value is the last observed value at the time the measurement was taken. 0 to 2.99 = Green 3.00 to 4.99 = Orange 5.00 = Red
Processor Time Instance	Percentage of time that the processor is executing application or operating system processes. This is when the processor is not idle.

Memory Performance Exchange 2010

Column	Description
Host	Name of the host where the Exchange server is installed.
Available Megabytes	Amount of physical memory immediately available for allocation to a process or for system use. 0 to 49.99 = Red 50 to 75.99 = Orange 76 to 99.99 = Yellow 100 = Green
Pool Paged Bytes	The portion of shared system memory that can be paged to the disk paging file.
Pool Nonpaged Bytes	System virtual addresses guaranteed to be resident in physical memory at all times and can thus be accessed from any address space without incurring paging input/output (I/O).
Cache Bytes	Size, in bytes, of the file system cache.

Transport Queues Exchange 2010

Column	Description
Host	Name of the host where the Exchange server is installed.
Aggregate Delivery Queue Length	Total number of items queued for delivery in all queues. 0.00 to 1500.99 = Green 1501.00 to 3000.99 = Yellow 3001.00 to 4000.99 = Orange 4001.00 to 5000 = Red
Active Mailbox Delivery Queue Length	Number of items in the active mailbox queues. 0 to 100 = Green 101 to 200 = Yellow 201 to 249 = Orange 250 = Red

Retry Mailbox Delivery	Number of items in the retry mailbox queues. 0 to 50 = Green 51 to 74 = Yellow 75 to 99 = Orange 100 = Red
Unreachable Queue Length	Number of items in the unreachable queues. 0 to 49 = Green 50 to 74 = Yellow 75 to 99 = Orange 100 = Red
Poison Queue Length	Number of items in the poison queue. 0.00 to 0.00 = Green 0.01 = Red
Messages Submitted per Second	Rate that messages are submitted by clients.
Messages Completed Delivery/Sec	Rate that messages are delivered to all recipients.

Exchange 2010 Domain Controllers Connectivity Counters

Column	Description
Host	Name of the host where the Exchange server is installed.
Searches/Second	Number of LDAP search requests issued per second.
Searches Timed Out/Minute	Number of LDAP searches that returned LDAP_Timeout during the last minute. 0 to 2.99 = Green 3 to 6.99 = Yellow 7 to 9.99 = Orange 10 = Red

Long Running LDAP Operations/Minute	<p>Number of LDAP operations on this domain controller that took longer than the specified threshold per minute.</p> <p>0 to 14.99 = Green</p> <p>15 to 24.99 = Yellow</p> <p>25 to 49.99 = Orange</p> <p>50 = Red</p>
-------------------------------------	--

Network Counters Exchange 2010

Column	Description
Host	Name of the host where the Exchange server is installed.
TCPv4 Connections Established	Number of TCP connections for which the state is either ESTABLISHED or CLOSE-WAIT. The number of TCP connections is constrained by the size of the nonpaged pool. When the nonpaged pool is depleted, no new connections can be established.
TCPv6 Connection Failures	Number of TCP connections for which the state is either ESTABLISHED or CLOSE-WAIT. The number of TCP connections is constrained by the size of the nonpaged pool. When the nonpaged pool is depleted, no new connections can be established.

Read Time Processes

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Read Time	Time to send an LDAP read request to the specified domain controller and receive a response.

Search Time Processes

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Search Time	Time to send an LDAP search request and receive a response.

.NET time in GC

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Time	When garbage collection has occurred. When the counter exceeds the threshold, the CPU is cleaning up and is not being used efficiently for load. Adding memory to the server would improve this situation.

.NET Exceptions Per Second

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Exceptions/sec	Number of exceptions thrown per second. These include both .NET framework exceptions and unmanaged exceptions that are converted into .NET framework exceptions.

.NET Bytes in All Heaps

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.

Bytes	Memory allocated in bytes on the GC heaps.
-------	--

Chapter 13: MS Exchange 2013

The MS Exchange Server 2010 Unified Dashboard provides pre-defined list views with information about your Microsoft Exchange server 2010, such as processor, memory performance, transport queues, domain controllers, .Net framework, and network counters.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[MS Exchange 2013 Required Data Sources](#) (see page 70)

[LDAP](#) (see page 72)

[Memory Counters](#) (see page 72)

[Memory Private Bytes](#) (see page 72)

[Memory Virtual Bytes](#) (see page 73)

[Network Counters Exchange 2013](#) (see page 73)

[Processor Counters Exchange 2013](#) (see page 73)

[Search Time Processes](#) (see page 74)

[Read Time Processes](#) (see page 74)

[.NET Exceptions Thrown](#) (see page 75)

[.NET time in GC](#) (see page 75)

[.NET Bytes in All Heaps](#) (see page 75)

MS Exchange 2013 Required Data Sources

The MS Exchange 2007 Unified Dashboard requires these probes:

- exchange_monitor
- exchange_monitor_backend
- perfmon
- processes
- ntevl

This table lists the QoS metrics and subkeys or targets that must be activated to populate data in the MS Exchange 2010 dashboard.

QoS Required	Subkey/Target
QOS_EXCHANGE_MEMORY_POOL_PAGED_BYTES	Pool Paged Bytes
QOS_EXCHANGE_MEMORY_CACHE_BYTES	Cache Bytes
QOS_EXCHANGE_PROCESSOR_USER_TIME	User Time
QOS_EXCHANGE_PROCESSOR_PRIVILEGED_TIME	Privileged Time
QOS_EXCHANGE_PROCESSOR_PROCESSOR_QUEUE_LENGTH	
QOS_EXCHANGE_PROCESSOR_PROCESSOR_TIME_INSTANCE	Processor Time Instance (processes)

QoS Required	Subkey/Target
QOS_EXCHANGE_NETWORK_TCPV4_CONNECTIONS_ESTABLISHED	TCPv4 Connections Established
QOS_EXCHANGE_NETWORK_TCPV6_CONNECTION_FAILURES	TCPv6 Connection Failures
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCHES_PER_SECOND	LDAP Searches Per Second(0)
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCHES_TIMED_OUT_PER_MINUTE	LDAP Searches Timed Out Per Minute
QOS_EXCHANGE_MSEXCHANGE_LDAP_SEARCH_TIME_PROCESSES	LDAP Search Time Processes
QOS_EXCHANGE_MSEXCHANGE_LDAP_READ_TIME_PROCESSES	LDAP Read Time Processes
QOS_EXCHANGE_MEMORY_DOTNET - TIME_IN_GC	
QOS_EXCHANGE_MEMORY_DOTNET - EXCEPTION_THROWN_PER_SEC	DOTNET - Exception Thrown Per Sec
QOS_EXCHANGE_MEMORY_PRIVATE_BYTES	Private Bytes
QOS_EXCHANGE_MEMORY_VIRTUAL_BYTES	Virtual Bytes
QOS_EXCHANGE_MEMORY_DOTNET - BYTES_IN_ALL_HEAPS	DOTNET - Bytes In All Heaps

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

LDAP

Column	Description
Host	Name of the host where the Exchange server is installed.
Searches/Second	Number of LDAP search requests issued per second.
Searches Timed Out/Minute	Number of LDAP searches that returned LDAP_Timeout during the last minute. 0 to 2.99 = Green 3 to 6.99 = Yellow 7 to 9.99 = Orange 10 = Red

Memory Counters

Column	Description
Host	Name of the host where the Exchange server is installed.
Host	Name of the host where the Exchange server is installed.
Pool Paged Bytes	The portion of shared system memory that can be paged to the disk paging file.
Cache Bytes	Size, in bytes, of the file system cache.

Memory Private Bytes

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Memory Private Bytes	Shows the current number of bytes this process has allocated that can't be shared with other processes.

Memory Virtual Bytes

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Memory Virtual Bytes	Represents (in bytes) how much virtual address space the process is currently consuming.

Network Counters Exchange 2013

Column	Description
Host	Name of the host where the Exchange server is installed.
TCPv4 Connections Established	Number of TCP connections for which the state is either ESTABLISHED or CLOSE-WAIT. The number of TCP connections is constrained by the size of the nonpaged pool. When the nonpaged pool is depleted, no new connections can be established.
TCPv6 Connection Failures	Number of TCP connections for which the state is either ESTABLISHED or CLOSE-WAIT. The number of TCP connections is constrained by the size of the nonpaged pool. When the nonpaged pool is depleted, no new connections can be established.

Processor Counters Exchange 2013

Column	Description
Host	Name of the host where the Exchange server is installed.
Processor User Time	Percentage of processor time spent in user mode. User mode is a restricted processing mode designed for applications, environment subsystems, and integral subsystems. 0 to 74.99 = Green 75 = Red

Processor Privileged Time	<p>Percentage of processor time spent in privileged mode.Privileged mode is a processing mode designed for operating system components and hardware-manipulating drivers. It allows direct access to hardware and all memory.</p> <p>0 to 74.99 = Green 75 = Red</p>
Processor Queue Length	<p>Number of threads each processor is servicing. Processor queue length can be used to identify whether processor contention or high CPU utilization is caused by the processor capacity being insufficient to handle the workload assigned to it.</p> <p>Processor Queue Length shows the number of threads that are delayed in the Processor Ready Queue and are waiting to be scheduled for execution. The listed value is the last observed value at the time the measurement was taken.</p> <p>0 to 2.99 = Green 3.00 to 4.99 = Orange 5.00 = Red</p>
Processor Time Instance	<p>Percentage of time that the processor is executing application or operating system processes.This is when the processor is not idle.</p>

Search Time Processes

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Search Time	Time to send an LDAP search request and receive a response.

Read Time Processes

Column	Description
Host	Name of the host where the Exchange server is installed.

Process	Target that is being monitored.
Read Time	Time to send an LDAP read request to the specified domain controller and receive a response.

.NET Exceptions Thrown

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Exceptions/sec	Number of exceptions thrown per second. These include both .NET framework exceptions and unmanaged exceptions that are converted into .NET framework exceptions.

.NET time in GC

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Time	When garbage collection has occurred. When the counter exceeds the threshold, the CPU is cleaning up and is not being used efficiently for load. Adding memory to the server would improve this situation.

.NET Bytes in All Heaps

Column	Description
Host	Name of the host where the Exchange server is installed.
Process	Target that is being monitored.
Bytes	Memory allocated in bytes on the GC heaps.

Chapter 14: MS SharePoint Server

The SharePoint Unified Dashboard provides predefined list views with information about your SharePoint server, such as CPU Performance and Memory usage, network utilization, disk usage and performance, and SQL server statistics.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[SharePoint Required Data Sources](#) (see page 77)

[CPU Performance](#) (see page 80)

[Memory Usage and Performance](#) (see page 80)

[ASP.NET](#) (see page 81)

[Network Utilization](#) (see page 81)

[Disk Usage and Performance](#) (see page 82)

[SQL Server Statistics](#) (see page 82)

[W3WP Process](#) (see page 83)

[Web Front End Server](#) (see page 83)

SharePoint Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the SharePoint dashboard.

Probe	QoS Required	Subkey/Target
sharepoint	QOS_%_PROCESSOR_TIME	MOSS2007 - CPU Total Processor Time_%Processor Time
	QOS_PROCESSOR_QUEUE_LENGTH	MOSS2007 - Processor Queue Length_Processor Queue Length
	QOS_BYTES_TOTAL/SEC	MOSS2007 - Network Interface - Total Bytes_Bytes Total/sec
	QOS_BYTES_SENT/SEC	MOSS2007 - Network Interface - Bytes Sent_Bytes sent/sec

Probe	QoS Required	Subkey/Target
sharepoint	QOS_%_PROCESSOR_TIME	MOSS2007 - CPU Total Processor Time_%Processor Time
	QOS_PROCESSOR_QUEUE_LENGTH	MOSS2007 - Processor Queue Length_Processor Queue Length
	QOS_BYTES_RECEIVED/SEC	MOSS2007 - Network Interface - Bytes Received_Bytes Received/sec
	QOS_PACKETS_OUTBOUND_ERRORS	MOSS2007 - Network Interface - Packets Outbound errors_Packets Outbound Errors
	QOS_%_USAGE	MOSS2007 - Paging File: %Usage_%Usage
	QOS_%_USAGE_PEAK	MOSS2007 - Paging File: %Usage Peak_%Usage Peak
	QOS_AVAILABLE_MBYTES	MOSS2007 - Availability of Memory in Bytes_Available
	QOS_PAGES/SEC	MOSS2007 - Memory_Pages Per Second_Pages/sec
	QOS_CACHE_FAULTS/SEC	MOSS2007 - Cache Faults Per Sec_Cache Faults/sec
	QOS_PAGE_FAULTS/SEC	MOSS2007 - Page Faults Per Second_Page Faults/sec
	QOS_BUFFER_CACHE_HIT_RATIO	MOSS2007 - SQL Server: Buffer Manager - Buffer Cache Hit Ratio_Buffer cache hit ratio
	QOS_CACHE_HIT_RATIO	MOSS2007 - SQL Server: Cache Hit Ratio_Cache Hit Ratio
	QOS_LATCH_WAITS/SEC	MOSS2007 - SQL Server: Latch Waits/sec_Latch Waits/sec
	QOS_NUMBER_OF_DEADLOCKS/SEC	MOSS2007 - SQL Server: Number of Deadlocks/sec_Number of Deadlocks/sec
	QOS_USER_CONNECTIONS	MOSS2007 - SQL Server: User Connections_User Connections
QOS_BYTES_SENT/SEC	MOSS2007 - Web Service - Bytes Sent Per Second_Bytes Sent/sec	

Probe	QoS Required	Subkey/Target
sharepoint	QOS_%_PROCESSOR_TIME	MOSS2007 - CPU Total Processor Time_%Processor Time
	QOS_PROCESSOR_QUEUE_LENGTH	MOSS2007 - Processor Queue Length_Processor Queue Length
	QOS_CURRENT_CONNECTIONS	MOSS2007 - Web Service_Current Connections
	QOS_CONNECTION_ATTEMPTS/SEC	MOSS 2007 - Web Service Connection Attempts_Connection Attempts/sec
	QOS_%_PROCESSOR_TIME	MOSS2007 - Process - W3WP Processor Time_%Processor Time
	QOS_WORKING_SET	MOSS2007 - Process - W3WP Working Set_Working Set
	QOS_REQUESTS_EXECUTING	MOSS2007 - ASP.NET Applications - Requests Executing_Requests Executing
	QOS_REQUEST_WAIT_TIME	MOSS2007 - ASP.NET Applications - Requests Wait Time_Request Wait Time
	QOS_REQUESTS/SEC	MOSS2007 - ASP.NET Applications_Requests/sec
	QOS_REQUESTS_REJECTED	MOSS2007 - ASP.NET Applications - Requests Rejected_requests Rejected

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

CPU Performance

Column	Description
Host	Name of the host where the SharePoint server is installed.
Processor Time Perc	Percentage of elapsed time the processor spends to execute a non-idle thread. 0 to 70 = Green 71 to 79 = Yellow 80 to 100 = Red
Processor Queue Length	If the threshold of this rule is exceeded, the processor is not fast enough.

Memory Usage and Performance

Column	Description
Host	Name of the host where the SharePoint server is installed.
Paging File Perc Usage and Perc used Peak	The server paging file, sometimes called the swap file, holds virtual memory addresses on disk. Page faults occur when a process has to stop and wait while required virtual resources are retrieved from disk into memory. Page faults are more frequent if physical memory is inadequate.
Avail MB	Amount of physical memory, in megabytes, immediately available for allocation to a process or for system use. Insufficient memory leads to excessive use of the page file and an increase in the number of page faults per second.
Pages/sec	Rate at which the pages are read from or written to disk to resolve hard page faults. A large number indicates system-wide performance problems. 0 to 7 = Green 8 to 9 = Yellow 10 = Red

Cache Faults/sec	Rate at which faults occur when a page is sought in the file system cache and is not found. This may be a soft fault when the page is found in memory or a hard fault when the page is on the disk. 0.0 to 0.99 = Green 1.0 = Red
Page Faults/sec	Number of times data was not found in memory. It measures the average number of pages faulted per second.

ASP.NET

Column	Description
Host	Name of the host where the SharePoint server is installed.
Requests Executing	Number of requests currently executing.
Request Wait Time	Number of milliseconds that the most recent request waited in the queue for processing. As the number of wait events increases, users experience degraded page-rendering performance.
Requests/sec	Number of requests executed per second. This represents the current throughput of the application. Under constant load, this number should remain within a certain range, barring other server work (such as garbage collection, cache cleanup thread, external server tools, and so on).
Req Queued	Number of requests waiting to be processed. 0 to 300 = Green 301 to 500 = Yellow 501 = Red
Requests Rejected	Total number of requests not executed because of insufficient server resources to process them. This counter represents the number of requests that return a 503 HTTP status code, indicating the server is too busy.

Network Utilization

Column	Description
Host	Name of the host where the SharePoint server is installed.

Bytes Total/sec	Rate at which the data is sent and received via the Network Interface Card. 0 to 39.9 = Green 40.0 to 49.9 = Yellow 50.0 = Red
Bytes Recd/sec	Rate at which data bytes are received by the web service.
Bytes Sent/sec	Rate at which data bytes are sent by the web service.
Packet Outbound Errors	Number of outbound packets that could not be transmitted because of errors.

Disk Usage and Performance

Column	Description
Host	Name of the host where the SharePoint server is installed.
Writes/sec	Number of writes to disk per second.
Reads/sec	Number of reads to disk per second.
Perc Idle Time	Percentage of time the disk system was not processing requests and no work was queued.
Avg Write Q Length	Average number of write requests that are queued.
Avg Read Q Length	Average number of read requests that are queued.
Avg Disk sec/Transfer	Number of read and writes completed per second, regardless of how much data they involve.

SQL Server Statistics

Column	Description
Host	Name of the host where the SharePoint server is installed.

Buffer Cache Hit Ratio	Percentage of pages found in the buffer cache without having to read from disk. The ratio is the total number of cache hits divided by the total number of cache lookups since an instance of SQL Server was started. 0.0 to 60.9 = Red 61.0 to 89.0 = Yellow 90.0 = Green
Cache Hit Ratio	Ratio between cache hits and lookups for plans.
Latch Waits/sec	Number of latch requests per second that could not be granted immediately.
Deadlocks/sec	Number of deadlocks on the SQL Server per second.
User Connections	Number of user connections on your instance of SQL Server.

W3WP Process

Column	Description
Host	Name of the host where the SharePoint server is installed.
Proc Time Perc	Percent of elapsed time that all process threads use the processor. 0.0 to 49.0 = Green 49.1 to 74.9 = Yellow 75.0 = Red
Working Set	The set of memory pages recently touched by the threads in the process. 0 to 79.0 = Green 80.0 = Red

Web Front End Server

Column	Description
Host	Name of the host where the SharePoint server is installed.
Bytes Sent/sec	Rate at which data bytes are sent by the web service.
Current Connections	Monitors current IIS connections.

Connection Attempts	Rate at which connections to the web service are attempted.
---------------------	---

Chapter 15: MS SQL Server

The MS SQL Server Unified Dashboard provides predefined list views with information about your MS SQL server, such as load, locks, performance reports and list designer, server processes, database performance and user statistics.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[MS SQL Server Required Data Sources](#) (see page 85)

[Performance Reports Designer](#) (see page 86)

[Server Load](#) (see page 86)

[Locks](#) (see page 87)

[MS SQL Server Processes](#) (see page 87)

[Database Performance](#) (see page 87)

[User Statistics](#) (see page 88)

MS SQL Server Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the IBM DS4K dashboard.

Probe	QoS	Subkey/Target
sqlserver	QOS_SQLSERVER_LOGIN_COUNT	*
	QOS_SQLSERVER_CHECK_DBALIVE	*
	QOS_SQLSERVER_TRANSACTIONS	*
	QOS_SQLSERVER_BUF_CACHEHIT_RATIO	*
	QOS_SQLSERVER_LOCK_WAITS	*
	QOS_SQLSERVER_LOCK_REQUESTS	*
	QOS_SQLSERVER_LOCK_TIMEOUTS	*
	QOS_SQLSERVER_ACTIVE_USERS	*
	QOS_SQLSERVER_BLOCKED_USERS	*
	QOS_SQLSERVER_SERVER_STARTUP	*

Probe	QoS	Subkey/Target
cdm	QOS_CPU_USAGE	*
processes	QOS_PROCESS_CPU	*
	QOS_PROCESS_MEMORY	*
	QOS_PROC_QUEUE_LEN	*

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Performance Reports Designer

This view allows you to see a visual representation of QoS data. You select the host, QoS measurement, target, and time range, and the data is displayed as a chart. You can display multiple measurements on a single chart, and can view multiple charts at a time. You can drag charts between rows or drag a data series from one chart to another. You can choose the chart format (line, area, or column chart), and the Filters tab allows you to plot only the data that matches specified filters on the chart. You can easily change the source (host or target) of the data by using the Choose Source menu. You can save a set of charts as a report to print or to view later. The import and export features allow you to share charts with other users.

Server Load

Column	Description
Host	Name of the host where the SQL server is installed.
Processor Queue Length 1 hr	Average number of processes queued for the SQL server during the past hour.
Current CPU Usage	Percent CPU used on the server. 0 to 80 = Green 80 to 90 = Orange 90 to 100 = Red

Locks

Column	Description
Host	Name of the host where the SQL server is installed.
Lock Waits	Monitors number of lock waits per second.
Lock Requests	Monitors number of lock requests per second.
Lock Timeouts	Monitors number of lock-timeouts per second. 0 to .79 = Green .8 to .99 = Yellow 1 and greater = Red

MS SQL Server Processes

Column	Description
Server	Name of the host where the SQL server is installed.
Process Name	Name of the SQL server process.
CPU	Percent of CPU consumed by the SQL process.
Memory	Number of kilobytes of memory consumed by the SQL process.

Note: To monitor data in the Server Processes view, you need to create a profile in the processes probe and configure it to monitor CPU and Memory QoS values.

Database Performance

Column	Description
Host	Name of the host where the SQL server is installed.
Status	Monitors connectivity to the database instance. Connection Up = Green Connection Down = Red
Transactions	Monitors the number of transactions per second.

Buffer Cache Hit Ratio	Monitors the buffer cache-hit ratio. 0 to 50.99 = Green 51 to 74.99 = Yellow 75 to 84.99 = Orange 85 to 100 = Red
Uptime	Monitors the uptime (in days) of the database server.

User Statistics

Column	Description
Host	Name of the host where the SQL server is installed.
Login Count	Monitors the number of users currently logged into the server.
Active Users	Monitors the number of active user per database.
Blocked Users	Monitors the number of users blocked.

Chapter 16: Network

The Network Unified Dashboard provides predefined list views with information about your network performance.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[Network Required Data Sources](#) (see page 89)

[Web Site Response Time](#) (see page 90)

[Cisco Device Health](#) (see page 90)

[Ping Response Time](#) (see page 90)

[Interface Bandwidth](#) (see page 91)

Network Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured Network dashboard.

Probe	QoS Required
interface_traffic	QOS_INTERFACE_TRAFFIC_PERC
net_connect	QOS_NET_CONNECT
url_response	QOS_URL_RESPONSE
cisco_monitor	QOS_MEMORY_USAGE QOS_CPU_USAGE

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Web Site Response Time

Column	Description
Monitored From	Name of the host with the Nimsoft url_response probe that is monitoring web site response time.
Profile Name	Name of the profile configured in the url_response probes. Typically this is the name of the web site.
Resp Time	Average time, in milliseconds, to receive a response to an HTTP GET request during the last hour.
Resp Time	Graph of average time, in milliseconds, to receive a response to an HTTP GET request during the last hour.
Alarm	Alarms generated by the url_response probe, if any.

Cisco Device Health

Column	Description
Host	IP address of the Cisco device.
Memory Used	Last reported number of megabytes of memory consumed by the Cisco device.
Memory Free	Last reported number of megabytes of memory available.
CPU Usage	Last reported percent of CPU consumed by the Cisco device.

Ping Response Time

Column	Description
Monitored From Host	Name of the host with the Nimsoft net_connect probe that is monitoring ping response time.
Host:Port	Name of the host and port number that the ping request was sent to.
Response Time	Last reported time, in milliseconds, to receive a response to the ping request.

Interface Bandwidth

Column	Description
Device	Name of the device where the interface is located.
Origin	QoS data from probes is tagged with a name to identify the origin of the data. The origin name is set in the controller probe GUI. If the origin name is not set, the hub name is used.
Interface	Type of interface.
Bandwidth	Last reported percent of bandwidth consumed by traffic on the interface.

Chapter 17: Power

The Data Center Power Unified Dashboard provides predefined list views with information about power usage in your data center.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [Power Required Data Sources](#) (see page 93)
- [UPS Battery Runtime Remaining](#) (see page 93)
- [Data Center Power Effectiveness](#) (see page 94)
- [Data Center Infrastructure Efficiency](#) (see page 94)
- [UPS Input Line Voltage](#) (see page 94)

Power Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured Power dashboard.

Probe	QoS Required
power	QOS_BATTERY_TIME_REMAINING QOS_DCIE QOS_PUE QOS_VOLTS

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

UPS Battery Runtime Remaining

Column	Description
Target	DataCenter plus the IP address, name, object identifier, or description of the data center.

Battery Runtime Remaining	Expected runtime of the UPS in minutes.
---------------------------	---

Data Center Power Effectiveness

Column	Description
Target	The data center name. For the current version of the power probe this is always Data Center.
PUE Value	Measurement of the energy efficiency of a data center. Calculated by dividing the total facility power by the total IT equipment power. PUE is the inverse of DCIE.
PUE Result	Efficiency level of measured PUE.

Data Center Infrastructure Efficiency

Column	Description
Target	DataCenter plus the IP address, name, object identifier, or description of the data center.
DCIE	Measurement of the energy efficiency of a data center. DCIE is calculated by dividing the total IT equipment power by the total facility power. DCIE is the inverse of PUE.
DCIE Results	Efficiency level of measured DCIE.

UPS Input Line Voltage

Column	Description
Name	DataCenter plus the IP address, name, object identifier, or description of the data center.
Volts	Voltage of the UPS input line.
Volts	Voltage of the UPS input line, displayed as a line graph.

Chapter 18: Server

The Server Unified Dashboard provides predefined list views with information about server performance, such as CPU, memory, disk space usage, and server load.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[Server Required Data Sources](#) (see page 95)

[Current Server Performance](#) (see page 95)

[Server Load 1 hour average](#) (see page 96)

[Server Disk Space Usage](#) (see page 96)

Server Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured Server dashboard.

Probe	QoS Required
cdm	QOS_CPU_USAGE QOS_PROC_QUEUE_LEN QOS_DISK_USAGE_PERC QOS_MEMORY_PERC_USAGE

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Current Server Performance

Column	Description
Host	Name of the server.
CPU Usage Last 6hr	Percent of CPU consumed over the last 6 hours.

CPU Usage	Percent of CPU in use.
Memory Usage	Percent of memory in use.

Server Load 1 hour average

Column	Description
Host	Name of the server.
1 hr Avg CPU Usage	Average percent of CPU consumed during the past hour.
1 hr Avg Proc Queue Length	Average number of processes queued during the past hour.

Server Disk Space Usage

Column	Description
Host	Name of the server.
Disk	Disk being monitored.
Percent Used	Percent of disk space consumed.

Chapter 19: Storage

The Storage unified dashboards provide out of the box dashboards with key performance and capacity information for storage devices.

You can use this data to spot potential performance issues and get an early warning of potential capacity issues and avoid downtime. The storage dashboard provides a unified view of various types of storage devices. The storage devices supported include the following:

- EMC Celerra series
- EMC Clariion series
- EMC VNX series
- EMC VMAX/DMX series

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[Storage Required Data Sources](#) (see page 98)

[Storage IOPS](#) (see page 100)

[Storage IO Data Rate](#) (see page 101)

[Storage Systems Status](#) (see page 101)

[Number of Storage Devices](#) (see page 101)

[Storage Systems Physical Disks](#) (see page 102)

Storage Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured Storage dashboard.

Probe	QoS Required
clariion	QOS_STORAGE_NUMBER_OF_DEVICES
netapp	QOS_STORAGE_DISK_CAPACITY
celerra	_STORAGE_SP_BLOCKS_READ_PER_SECOND
vmax	_STORAGE_DISK_READ
ibm	System Statistics.Disk Read
compellent	_STORAGE_DISK_READ_KB_PER_SEC
Note: Not all of these probes are required. The reports look for one or more of the probes if they exist.	System Statistics.Disk Read
	_STORAGE_SP_BLOCKS_READ_PER_SECOND
	SP B
	_STORAGE_SP_BLOCKS_READ_PER_SECOND
	SP A
	_STORAGE_SP_BLOCKS_READ_PER_SECOND
	SP A
	_STORAGE_SP_BLOCKS_READ_PER_SECOND
	SP B
	_STORAGE_SP_BLOCKS_READ_PER_SECOND
	SP A
	_STORAGE_DISK_READ
	System Statistics.Disk Read
	_STORAGE_DISK_READ
	System Statistics.Disk Read
_STORAGE_DISK_READ	
System Statistics.Disk Read	
_STORAGE_DISK_WRITE	
System Statistics.Disk Write	
_STORAGE_DISK_WRITE_KB_PER_SEC	
System Statistics.Disk Write	

Probe	QoS Required
<i>(continued)</i>	_STORAGE_SYMM_DISK_KB_WRITE_PER_SEC System Statistics.Disk Write _STORAGE_SYMM_DISK_KB_WRITE_PER_SEC System Statistics.Disk Write _STORAGE_DISK_WRITE System Statistics.Disk Write _STORAGE_DISK_WRITE System Statistics.Disk Write _STORAGE_DISK_WRITE System Statistics.Disk Write _STORAGE_IOPS System Statistics.IOPS _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_WRITE_IOPS SP A _STORAGE_SP_WRITE_IOPS SP A _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_WRITE_IOPS SP A _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_WRITE_IOPS SP B _STORAGE_SP_READ_IOPS SP B _STORAGE_SP_WRITE_IOPS SP A _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_WRITE_IOPS SP B _STORAGE_SP_READ_IOPS SP B _STORAGE_SP_WRITE_IOPS Unknown _STORAGE_SP_READ_IOPS Unknown _STORAGE_SP_WRITE_IOPS SP B
	_STORAGE_SP_WRITE_IOPS SP A

Probe	QoS Required
(continued)	_STORAGE_SP_READ_IOPS SP B _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_READ_IOPS SP B _STORAGE_SP_WRITE_IOPS SP B _STORAGE_SP_READ_IOPS SP A _STORAGE_SP_WRITE_IOPS SP A _STORAGE_IOPS System Statistics.IOPS _STORAGE_IOPS System Statistics.IOPS _STORAGE_IOPS System Statistics.IOPS

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Storage IOPS

This view displays the I/O performance of a storage system as the number of I/O operations per second. This performance metric is critical to understanding bottlenecks or throughput in a storage array system.

Chart	Description
Storage IOPS	This chart portrays the overall Number of I/O operations per second for every storage array.

Storage IO Data Rate

This view displays the overall data bandwidth measured as average disks read and write (I/O) data rate in kilobits (Kb) per second of all discovered storage systems.

Chart	Description
Disks Reads Kb/sec	This displays overall disk data reads in Kb per sec for each discovered and monitored storage system. This indicates storage bandwidth and speed of Data access.
Disks Writes Kb/Sec	This displays overall disk data writes in Kb per sec for each discovered and monitored storage system. This indicates storage bandwidth and speed of Data storage.

Storage Systems Status

This view displays the status of all discovered storage systems.

Column	Description
Storage Systems	This lists the host or controller IP address of host name of all discovered and monitored storage systems.
Alarm Status	This shows the Nimsoft alarms from all discovered and monitored storage systems with standard color scheme pertaining to severity.

Number of Storage Devices

This list view displays the number of storage devices in each discovered storage system.

Column	Description
Storage Systems	This lists the host name or IP address of each discovered and monitored storage system.
Storage Array	This lists the storage array names from the above storage systems.
Total Storage Devices	This lists the number of logical storage devices i.e. LUNs in the above storage systems.

Storage Systems Physical Disks

This list view displays the number of physical disks in each discovered storage system.

Columns	Description
Storage Systems	This lists the host name or IP address of each discovered and monitored storage system.
Physical Storage	This lists the storage array or chassis/enclosure name of each discovered and monitored storage system.
Total Disks Count	This lists the number of physical disks discovered in each storage array or chassis/enclosure name of each discovered and monitored storage system.

Chapter 20: Vblock

The Vblock Unified Dashboard provides six predefined list views with performance and status information about Vblock Infrastructure Platforms.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

[Vblock Required Data Sources](#) (see page 104)

[Vblock Storage Performance](#) (see page 110)

[Vblock UCS Performance](#) (see page 111)

[Vblock Nexus Switch Performance](#) (see page 111)

[Vblock Host Summary](#) (see page 111)

[Vblock Datastore Freespace](#) (see page 112)

[Vblock Guest Summary](#) (see page 112)

Vblock Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured Vblock dashboard.

Probe	QoS Required
vmware clariion cisco_ucs interface_traffic Note: Not all of these probes are required. The reports look for one or more of the probes if they exist.	QOS_INTERFACE_TRAFFIC IN-Vethernet1Nexus 1K IN-Vethernet2Nexus 1K IN-Vethernet3Nexus 1K IN-Vethernet4Nexus 1K IN-Vethernet5Nexus 1K IN-Vethernet6Nexus 1K IN-Vethernet7Nexus 1K IN-Vethernet8Nexus 1K IN-Vethernet9Nexus 1K IN-Vethernet10Nexus 1K IN-Vethernet12Nexus 1K IN-Vethernet15Nexus 1K IN-Vethernet17Nexus 1K IN-Vethernet18Nexus 1K IN-Vethernet19Nexus 1K IN-Vethernet20Nexus 1K

Probe	QoS Required
<i>(continued)</i>	QOS_INTERFACE_TRAFFIC OUT-Vethernet1Nexus 1K OUT-Vethernet2Nexus 1K OUT-Vethernet3Nexus 1K OUT-Vethernet4Nexus 1K OUT-Vethernet5Nexus 1K OUT-Vethernet6Nexus 1K OUT-Vethernet7Nexus 1K OUT-Vethernet8Nexus 1K OUT-Vethernet9Nexus 1K OUT-Vethernet10Nexus 1K OUT-Vethernet12Nexus 1K OUT-Vethernet15Nexus 1K OUT-Vethernet17Nexus 1K OUT-Vethernet18Nexus 1K OUT-Vethernet19Nexus 1K OUT-Vethernet20 QOS_STORAGE_SP_PCT_BUSY SP A SP B

Probe	QoS Required
<i>(continued)</i>	<p>QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPA FAST Cache</p> <p>QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPB FAST Cache</p> <p>QOS_STORAGE_SP_PCT_DIRTY SP A</p> <p>QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPB FAST Cache</p> <p>QOS_STORAGE_FAST_CACHE_PCT_DIRTY_SPA FAST Cache</p> <p>QOS_STORAGE_TP_PERCENT_SUBSCRIBED DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool</p> <p>QOS_STORAGE_TP_PERCENT_AVAILABLE DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool</p> <p>QOS_STORAGE_TP_PERCENT_FULL DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool</p> <p>QOS_STORAGE_TP_SUBSCRIBED_CAPACITY DQA-FC-01</p> <p>QOS_STORAGE_TP_AVAILABLE_CAPACITY DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool</p>

Probe	QoS Required
<i>(continued)</i>	QOS_STORAGE_TP_SUBSCRIBED_CAPACITY DQA-GP-01 Prod-GP-01 Test_Pool QOS_STORAGE_TP_CONSUMED_CAPACITY DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool QOS_STORAGE_TP_USER_CAPACITY DQA-FC-01 DQA-GP-01 Prod-GP-01 Test_Pool QOS_UCS_POWER Consumed Power (sys/chassis-1/blade-1/board/power-stats) Consumed Power (sys/chassis-1/blade-6/board/power-stats) Consumed Power (sys/chassis-1/blade-5/board/power-stats) Consumed Power (sys/chassis-1/blade-7/board/power-stats) Consumed Power (sys/chassis-1/blade-8/board/power-stats) QOS_UCS_POWER Consumed Power (sys/chassis-2/blade-1/board/power-stats) Consumed Power (sys/chassis-2/blade-2/board/power-stats) Consumed Power (sys/chassis-2/blade-3/board/power-stats) Consumed Power (sys/chassis-2/blade-4/board/power-stats) Consumed Power (sys/chassis-2/blade-5/board/power-stats) Consumed Power (sys/chassis-2/blade-6/board/power-stats) Consumed Power (sys/chassis-2/blade-7/board/power-stats) Consumed Power (sys/chassis-2/blade-8/board/power-stats)
	QOS_UCS_POWER Consumed Power (sys/chassis-3/blade-6/board/power-stats) Consumed Power (sys/chassis-3/blade-7/board/power-stats)

Probe	QoS Required
<i>(continued)</i>	QOS_UCS_PERFORMANCE Available Memory (sys/switch-A/sysstats)
	QOS_UCS_PERFORMANCE Available Memory (sys/switch-B/sysstats)VSC101F140
	QOS_UCS_PERFORMANCE Available Memory (sys/switch-A/sysstats)VSC101F140
	QOS_UCS_PERFORMANCE Available Memory (sys/switch-B/sysstats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-2/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-1/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-1/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-2/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-1/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-1/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-2/fan-2/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-1/stats)
	QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-3/fan-2/stats)
QOS_UCS_FAN_SPEED Speed (sys/chassis-2/fan-module-1-1/fan-1/stats)	

Probe	QoS Required
<i>(continued)</i>	<p>QOS_UCS_FAN_SPEED Speed (sys/chassis-1/fan-module-1-1/fan-1/stats)</p> <p>QOS_MEMORY_PERC_USAGE Resources.MemoryOverallUsage (% of MemoryMaxUsage)</p> <p>QOS_CPU_USAGE Resources.CPUOverallUsage (% of CPUMaxUsage)</p> <p>QOS_MEMORY_PERC_USAGE Memory Usage</p> <p>QOS_CPU_USAGE CPU Usage (Average/Rate)</p> <p>QOS_NETWORK_BYTES_RECEIVED_PER_SECOND Network Data Receive Rate</p> <p>QOS_NETWORK_BYTES_SENT_PER_SECOND Network Data Transmit Rate</p> <p>QOS_DISK_READ_REQUEST Disk Read Requests</p> <p>QOS_DISK_WRITE_REQUEST Disk Write Requests</p> <p>QOS_DISK_READ Disk Read Rate</p> <p>QOS_DISK_WRITE Disk Write Rate</p> <p>QOS_DISK_LATENCY Disk Latency</p>

Probe	QoS Required
(continued)	QOS_DS_DISK_FREE QOS_VMWARE_VARIABLE PowerState QOS_MEMORY_PERC_USAGE GuestMemoryUsage (in % of Memory) QOS_MEMORY_PERC_USAGE HostMemoryUsage (in % of Memory) QOS_COUNTER VMCountActive VMCount QOS_MEMORY_PERC_USAGE Memory Usage

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Vblock Storage Performance

This view displays health and thin pool usage information for the EMC Clariion Storage component of the Vblock Infrastructure Platform.

Chart	Description
Storage Processors (SP) Utilization in %	Percent of SP A and SP B utilization for the entire Vblock Infrastructure Platform storage processed through SP A and SP B.
Dirty Cache % (Fast Cache)	Dirty cache as a percent of total for each storage processor in the Clariion component of the Vblock Infrastructure Platform.
Thin Pool Usage %	Percent of allocated thin pool that is subscribed for each thin pool in the Clariion component of the Vblock Infrastructure Platform.
Thin Pool Capacity in GB	Thin pool capacity, in GB, for subscribed and available capacities for each thin pool in the Clariion component of the Vblock Infrastructure Platform.

Vblock UCS Performance

This view displays environment and power information for the Cisco Unified Computing System (UCS) component of the Vblock Infrastructure Platform.

Chart	Description
Consumed Power	Number of watts of consumed power for each blade server in each UCS chassis.
Temperature	Ambient temperature in Celsius for each blade server in each UCS chassis.
Fabric Interconnect - Available Memory	Number of megabytes of available memory for each UCS Fabric Interconnect in the Vblock Infrastructure Platform.
Fan Speed	Fan speed, in RPM, for each fan in each fan module of each UCS chassis.

Vblock Nexus Switch Performance

This view displays network throughput information for the Cisco Nexus Virtual Switch component of the Vblock Infrastructure Platform.

Chart	Description
Network Traffic Incoming	Number of incoming bytes per second for each virtual Ethernet port in the Nexus Virtual Switch.
Network Traffic Outgoing	Number of outgoing bytes per second for each virtual Ethernet port in the Nexus Virtual Switch.

Vblock Host Summary

This view displays performance information about virtual hosts resources.

Column	Description
VMware Host	Name of the host in the Vblock Infrastructure Platform.
VM Count Active	Number of virtual machines active on the host.
VM Count	Number of virtual machines configured on the host.

CPU Usage	Percent of CPU in use. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Memory Usage	Percent of memory in use. 0 to 69.99 = Green 70 to 89.99 = Yellow 90 to 100 = Red

Vblock Datastore Freespace

This view displays performance and status information about virtual datastore resources.

Column	Description
Host	The host where the datastore resides in the Vblock Infrastructure Platform.
Datastore Name	The name of the datastore.
Free Space	Percent of free disk space available.
Datastore Status	Amount of free space in the datastore. <ul style="list-style-type: none"> ■ Very low = 0-2% ■ Low = 2.1-5% ■ OK = 5.1-100%

Vblock Guest Summary

This view displays performance and status information about virtual guest resources.

Column	Description
Guest	Lists the virtual machines (guests) configured in your Vblock Infrastructure Platform environment.
Power Status	Whether the guest is powered on, off, or on standby.
CPU Usage	Number of megahertz of CPU consumed by the guest.

Memory Usage	Percent of memory consumed on the guest. This could exceed 100 percent if additional resources are consumed.
Host Memory Usage	Percent of memory consumed on the host.
Alarm	Lists alarms for the guest.

Chapter 21: VCloud

The VCloud Unified Dashboard provides six predefined list views for monitoring Virtual Data Centers (VDCs). The first three list views monitor memory, CPU, and storage on the organizational VDCs. The last three list views monitor memory, CPU, and storage on the provider VDCs. For organizational VDCs the usages are displayed as percent of the limit. For the provider VDCs the usages are displayed as percent of the capacity.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [VCloud Required Data Sources](#) (see page 115)
- [VCloud Organization VDCs CPU Used Percent](#) (see page 116)
- [VCloud Organization VDCs Memory Used Percent](#) (see page 116)
- [VCloud Organization VDCs Storage Used Percent](#) (see page 117)
- [VCloud Provider VDCs CPU Used Percent](#) (see page 118)
- [VCloud Provider VDCs Memory Used Percent](#) (see page 118)
- [VCloud Provider VDCs Storage Used Percent](#) (see page 119)

VCloud Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured VCloud dashboard. The UMP Dashboards template, found in the vcloud probe configuration UI, includes these QoS measurements and is provided to assist you in configuring the vcloud probe for the dashboard.

Probe	QoS Required
vcloud	QOS_ORG_VDC_STORAGE_USED_PCT
	QOS_PROV_VDC_MEMORY_USED_PCT
	QOS_PROV_VDC_CPU_USED_PCT
	QOS_PROV_VDC_STORAGE_USED_PCT
	QOS_ORG_VDC_MEMORY_USED_PCT
	QOS_ORG_VDC_CPU_USED_PCT

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

VCloud Organization VDCs CPU Used Percent

This view displays CPU usage information for your organization's virtual datacenters (VDCs).

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Organization VDCs	Name of the organization VDC managed by the vCloud Director.
CPU Used Last Hour Percent	CPU (as percent of limit) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
CPU Used Last 24 Hours Percent	CPU (as percent of limit) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

VCloud Organization VDCs Memory Used Percent

This view displays memory usage information for your organization's virtual datacenters (VDCs).

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Organization VDCs	Name of the organization VDC managed by the vCloud Director.

Memory Used Last Hour Percent	Memory (as percent of limit) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
Memory Used Last 24 Hours Percent	Memory (as percent of limit) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

VCloud Organization VDCs Storage Used Percent

This view displays storage usage information for your organization's virtual datacenters (VDCs).

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Organization VDCs	Name of the organization VDC managed by the vCloud Director.
Storage Used Last Hour Percent	Storage (as percent of limit) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
Storage Used Last 24 Hours Percent	Storage (as percent of limit) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

VCloud Provider VDCs CPU Used Percent

This view displays CPU usage information for the virtual datacenters (VDCs) you use that are provided by your cloud services provider.

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Provider VDCs	Name of the provider VDC managed by the vCloud Director.
CPU Used Last Hour Percent	CPU (as percent of capacity) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
CPU Used Last 24 Hours Percent	CPU (as percent of capacity) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

VCloud Provider VDCs Memory Used Percent

This view displays memory usage information for the virtual datacenters (VDCs) you use that are provided by your cloud services provider.

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Provider VDCs	Name of the provider VDC managed by the vCloud Director.

Memory Used Last Hour Percent	Memory (as percent of capacity) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
Memory Used Last 24 Hours Percent	Memory (as percent of capacity) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

VCloud Provider VDCs Storage Used Percent

This view displays storage usage information for the virtual datacenters (VDCs) you use that are provided by your cloud services provider.

Column	Description
VCloud Director Host	IP address or name of host where the VMware vCloud Director software is running.
VCloud Director Provider VDCs	Name of the provider VDC managed by the vCloud Director.
Storage Used Last Hour Percent	Storage (as percent of capacity) used during the last hour for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red
Storage Used Last 24 Hours Percent	Storage (as percent of capacity) used during the last 24 hours, displayed in 1-hour increments, for the systems in the VDC. 0 to 70 = Green 70 to 80 = Yellow 80 to 90 = Orange 90 and above = Red

Chapter 22: VMware

The VMware Unified Dashboard provides predefined list views with usage and performance data about VMware hosts and virtual machines in your environment.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [VMware Required Data Sources](#) (see page 121)
- [VMware Host VM Count](#) (see page 123)
- [VMware Guests](#) (see page 126)
- [VMware Datastore Free Space](#) (see page 130)
- [VMware Resource Pools](#) (see page 130)

VMware Required Data Sources

This table lists the probes, QoS metrics, and subkeys or targets that must be activated to populate data in the VMware dashboard.

Probe	QoS	Subkey/Target
vmware	QOS_MEMORY_PERC_USAGE	Memory Granted (% of MemorySize) Memory Reserved Capacity (% of MemorySize) Resources.MemoryOverallUsage (% of MemoryMaxUsage) Memory Usage GuestMemoryUsage (in % of Memory) HostMemoryUsage (in % of Memory) Memory Balloon (% of MemorySize) Memory Swapped (% of Memory) Memory Swapped (% of MemorySize)
	QOS_DS_DISK_FREE	Free (in % of Capacity)

Probe	QoS	Subkey/Target
	QOS_CPU_USAGE	Resources.CPUOverallUsage (% of CPUMaxUsage) CPU Reserved Capacity (% of mhz*NumCpuCores) CPU Usage (Average/Rate) CPU Used (% of available) CPU Ready (% of available)
	QOS_COUNTER	VMCount VMCountActive
	QOS_VMWARE_VARIABLE	PowerState ToolsVersionStatus ToolsRunningStatus NumCPU
	QOS_VMWARE_VM_MEMORY_SWAP_OUT_RATE	Memory Swap Out Rate
	QOS_VMWARE_VM_MEMORY_SWAP_IN_RATE	Memory Swap In Rate
	QOS_VMWARE_VM_MEMORY_DECOMPRESSION_RATE	Memory Decompression Rate
	QOS_VMWARE_VM_MEMORY_COMPRESSION_RATE	Memory Compression Rate
	QOS_VMWARE_VM_DISK_AGGREGATE_MAX_TOTAL_LATENCY	Disk Highest Latency
	QOS_VMWARE_VM_CPU_SWAP_WAIT	CPU Swap Wait (% of available)
	QOS_VMWARE_HOST_NUM_VMS_HIGH_READY	Num VMs With High Ready
	QOS_VMWARE_HOST_NUM_VMS_BALLOONING	Num VMs Ballooning
	QOS_VMWARE_HOST_NUM_VMS_HIGH_READY	Num VMs With High Ready
	QOS_VMWARE_HOST_NUM_VMS_BALLOONING	Num VMs Ballooning
	QOS_VMWARE_HOST_NIC_AGGREGATE_TRANSMITS_DROPPED	Network Transmit Packets Dropped
	QOS_VMWARE_HOST_NIC_AGGREGATE_RECEIVES_DROPPED	Network Receive Packets Dropped

Probe	QoS	Subkey/Target
	QOS_VMWARE_HOST_MEMORY_SWAP_OUT_RATE	Memory Swap Out Rate
	QOS_VMWARE_HOST_MEMORY_SWAP_IN_RATE	Memory Swap In Rate
	QOS_VMWARE_HOST_MEMORY_DECOMPRESSION_RATE	Memory Decompression Rate
	QOS_VMWARE_HOST_MEMORY_COMPRESSION_RATE	Memory Compression Rate
	QOS_VMWARE_HOST_DISK_AGGREGATE_MAX_TOTAL_LATENCY	Disk Highest Latency
	QOS_NETWORK_BYTES_SENT_PER_SECOND	Network Data Transmit Rate
	QOS_NETWORK_BYTES_RECEIVED_PER_SECOND	Network Data Receive Rate
	QOS_DISK_WRITE	Disk Write Rate
	QOS_DISK_READWRITE	Disk Usage
	QOS_DISK_READ	Disk Read Rate
	QOS_DISK_FREE	Free (in % of Capacity)
	QOS_DISK_COMMANDS_ABORTS	Disk Commands Aborts

An asterisk (*) means that the value for the first entry for the QoS is used. The asterisk should only be used when the QoS metric for a probe is known to return only one value.

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

VMware Host VM Count

VMware Host VM Count

Column	Description
VMware Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
VM Count Active	Number of virtual machines active on the host.

VM Count	Number of virtual machines configured on the host.
CPU Usage	Percent of CPU in use. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Memory Usage	Percent of memory in use. 0 to 69.99 = Green 70 to 89.99 = Yellow 90 to 100 = Red

VMware Host CPU Summary

Column	Description
Host	Lists the hosts (not the virtual machines) in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Average Usage	Average CPU usage. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Overall Usage	Percent of CPU Max used. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Reserved Capacity	Percent of reserved capacity in use. Calculated as percent of megahertz times the number of CPU cores.

VMware Host Memory Summary

Column	Description
Host	Name or IP address of the host. Click the name of a host to view a Performance Report of performance data for that host.
Used	Percent of memory used on host. 0 to 69.99 = Green 70 to 89.99 = Yellow 90 to 100 = Red
Granted	Percent of total memory of all types in use. 0 to 79.99 = Green 80 to 89.99 = Yellow 90 to 109.00 = Orange 110 or greater = Red
Reserved Capacity	Percent of reserved memory capacity in use. 0 to 89.99 = Green 90 to 100 = Red
Balloon	Percent of memory balloon in use. The memory balloon is memory allotted for the host to expand to if needed. 0 to 89.99 = Green 90 to 100 = Red

VMware Host Disk Summary

Column	Description
Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Disk Read Rate	Rate, in kilobytes per second, at which data is read from disk by the host. Always green.
Disk Write Rate	Rate, in kilobytes per second, at which data is written to disk by the host. Always green.

Highest Disk Latency	Highest latency value, in milliseconds, across all disks used by the host. 0 to 50 = Green 50+ = Red
Disk Command Aborts	Number of commands aborted per second. 0 to 0 = Green .01+ = Red

VMware Host Network Summary

Column	Description
VMware Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Network Receive Packets Dropped	Number of incoming packets dropped during the last collection period. 0 to 1 = Green 1+ = Red
Network Transmit Packets Dropped	Number of outgoing packets dropped during the last collection period. 0 to 1 = Green 1+ = Red
Data Receive Rate	Rate, in kilobytes per second, at which the host receives data.
Data Transmit Rate	Rate, in kilobytes per second, at which the host transmits data.

VMware Guests

VMware Guest Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.

Power Status	Whether the guest is powered on, off, or on standby. Red = Power Off Cyan = Suspended Green = Power On
CPU Usage	Percent of megahertz of CPU consumed by the guest. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red
Memory Usage	Percent of memory consumed on the guest. This could exceed 100 percent if additional resources are consumed. 0 to 69.99 = Green 70 to 89.99 = Orange 90 or greater = Red
Host Memory Usage	Percent of memory consumed on the host. 0 to 79.99 = Green 80 to 89.99 = Yellow 90 to 109.99 = Orange 110 or greater = Red
Alarm	Lists alarms for the guest.

VMware Guest CPU Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.
#vCPUs	Number of CPUs in this virtual machine.
CPU Ready	Percent of time the virtual machine was ready but could not get scheduled to run on the physical CPU.
CPU Swap Wait	Percent of CPU time spent waiting for swap-in.
CPU Usage	Percent of megahertz of CPU consumed by the guest. 0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red

VMware Guest Memory Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.
Memory Swapped	Percent of guest physical memory swapped out to the virtual machine's swap file by the VMkernel.
Memory Balloon	Percent of memory allocated by the virtual machine memory control driver (vmmemctl), which is installed with VMware Tools. 0 to .1 = Green .1 to 100 = Red
Memory Usage	Percent of memory used on guest. 0 to 69.99 = Green 70 to 89.99 = Yellow 90 to 100 = Red

VMware Guest Disk Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.
Disk Command Aborts	Number of commands aborted per second. 0 to 0 = Green .01+ = Red
Disk Usage in KBps	Aggregated disk I/O rate. Always green.
Highest Disk Latency in ms	Highest latency value, in milliseconds, across all disks used by the guest. 0 to 50 = Green 50+ = Red

VMware Guest Network Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.
Network Receive Packets Dropped	Number of incoming packets dropped during the last collection period. 0 to 1 = Green 1+ = Red
Network Transmit Packets Dropped	Number of outgoing packets dropped during the last collection period. 0 to 1 = Green 1+ = Red
Data Receive Rate	Rate, in kilobytes per second, at which the guest receives data.
Data Transmit Rate	Rate, in kilobytes per second, at which the guest transmits data.

VMware Guest Tools Summary

Column	Description
Guest	Lists the virtual machines (guests) configured in your environment.
Power Status	Whether the guest is powered on, off, or on standby. Red = Power Off Cyan = Suspended Green = Power On
Tools Running Status	Current status of VMware Tools running in the guest operating system. Red = Not running Green = Running Blue = Starting

Tools Version Status	<p>Current version status of VMware Tools in the guest operating system.</p> <p>Red = Not installed</p> <p>Green = Current</p> <p>Blue = Unmanaged</p> <p>Orange = Need upgrade</p>
----------------------	---

VMware Datastore Free Space

Column	Description
Host	The host where the datastore resides.
Datastore Name	The name of the datastore.
Free Space	<p>Percent of free disk space available.</p> <p>0 to 1.99 = Red</p> <p>2 to 4.99 = Orange</p> <p>5 to 100 = Green</p>
Status	<p>Amount of free space in the datastore:</p> <p>Very low = 0-2% (Red)</p> <p>Low = 2.1-5% (Orange)</p> <p>OK = 5.1-100% (Green)</p>

VMware Resource Pools

VMware Resource Pool CPU Usage

Column	Description
Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Resource Pool	Lists the resource pools in your environment. Click the name of a resource pool to view a Performance Report of overall CPU usage for that resource pool.

CPU Usage	<p>Close to real-time resource usage of all running child virtual machines, including virtual machines in child resource pools. Expressed as a percent of current upper bound on usage.</p> <p>0 to 94.99 = Green 95 to 96.99 = Yellow 97 to 98.99 = Orange 99 to 100 = Red</p>
-----------	--

VMware Resource Pool Memory Usage

Column	Description
Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Resource Pool	Lists the resource pools in your environment. Click the name of a resource pool to view a Performance Report of overall memory usage for that resource pool.
Memory Usage	<p>Close to real-time resource usage of all running child virtual machines, including virtual machines in child resource pools. Expressed as a percent of current upper bound on usage.</p> <p>0 to 69.99 = Green 70 to 89.99 = Orange 90 to 100 = Red</p>

VMware Resource Pool Ballooning Status

Column	Description
Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Resource Pool	Lists the resource pools in your environment. Click the name of a resource pool to view a Performance Report of guest ballooning count for that resource pool.
Num VMs Ballooning	Number of VMs on this host with memory ballooning. Always green.

VMware Resource Pool Ready Summary

Column	Description
Host	Lists the VMware hosts in your environment. Click the name or IP address of a host to view a Performance Report of performance data for that host.
Resource Pool	Lists the resource pools in your environment. Click the name of a resource pool to view a Performance Report of guest high ready CPU count for that resource pool.
Num VMs High Ready	Number of VMs on this host with CPU Ready higher than 10 percent. Always green.

Chapter 23: Xenserver

The XenServer Unified Dashboard provides six predefined list views for monitoring XenServer servers. The views include metrics about CPU usage, network performance, VM memory, host memory, and disk usage and performance.

Note: If your Unified Dashboard is not populating with data, make sure all required data sources for the Unified Dashboard are enabled. The required probe must be deployed and must be configured so that required QoS metrics and subkeys or targets are activated. For more information, see the help topic on required data sources for the Unified Dashboard.

This section contains the following topics:

- [Xenserver Required Data Sources](#) (see page 133)
- [Xenserver CPU Metrics](#) (see page 134)
- [Xenserver Network Metrics](#) (see page 134)
- [Xenserver Memory Metrics VM](#) (see page 135)
- [Xenserver Memory Metrics Host](#) (see page 135)
- [Xenserver Disk Metrics](#) (see page 135)
- [Xenserver Disk Usage Percentage](#) (see page 136)

Xenserver Required Data Sources

The table contains the probes and QoS metrics required for the preconfigured XenServer dashboard.

The UMP Dashboards template, found in the xenserver probe configuration UI, includes these QoS measurements and is provided to assist you in configuring the xenserver probe for the dashboard.

Probe	QoS Required
xenserver	

For more information on configuring probes, see the documentation for each probe. This is available from the Nimsoft Product Information Library at <http://docs.nimsoft.com>.

Xenserver CPU Metrics

This chart displays information about CPU usage on the XenServer host.

Column	Description
Host	IP address or name of host where XenServer is running.
Host CPU Avg Utilization	Average percent of CPU used on the host.
Total Virtual CPU Utilization	Total CPU used on the VMs, in percent.
CPU Speed	CPU processing speed

Xenserver Network Metrics

This chart displays information about network performance.

Column	Description
Host	IP address or name of the host where XenServer is running.
Network_Status	Status of the network.
KBytes Transmitted	Kilobytes per second transmitted.
KBytes Received	Kilobytes per second received.

Xenserver Memory Metrics VM

This chart displays information about memory usage on the VMs.

Column	Description
Host	IP address or name of host
Free Memory	Amount of free memory, in megabytes, on the VM.
Total Memory	Total amount of memory, in megabytes, allocated to the VM.
Used Memory	Used memory, in megabytes, on the VM.
Actual Memory	Actual memory, in megabytes, on the VM.
Target Memory	

Xenserver Memory Metrics Host

This chart displays information about memory usage on the XenServer host.

Column	Description
Host	IP address or name of the host where XenServer is running.
Source	
Free Memory	Free memory, in megabytes, on the host.
Total Memory	Total memory, in megabytes, on the host.
Used Memory	Percent of memory used on the XenServer host.

Xenserver Disk Metrics

This chart displays information about disk performance.

Column	Description
Host	IP address or name of the host.
Read Throughput	Read rate, in kilobytes per second.
Write Throughput	Write rate, in kiloytes per second.

Column	Description
Virtual Block Device Size	

Xenserver Disk Usage Percentage

This chart displays information about disk usage.

Column	Description
Target	
Source	
Disk Space Percentage	Amount of used space on the disk.